

Angular Contact Bearing Swivels



Product information

- YOKE Swivels are manufactured using the highest grade of material available.
- YOKE Swivels are available in sizes from 3/4 tonnes to 25 tonnes.
- YOKE Swivels are available for wire lines 1/4" to 1-1/2".
- YOKE Swivels are zinc plated for corrosion resistance and longer life.
- YOKE Swivels are manufactured with grease fittings for superior performance.
- YOKE Swivels are designed for low starting torque and high rotation speed.
- All Swivels parts are 100% magnaflux crack detected.
- 20,000 cycle fatigue rate to 1.5 times working load limit.
- All parts with batch number for quality certified and traceability.
- Minimum Ultimate Load is 5 times the Working Load Limit. Maximum Proof Load is 2 times the Working Load Limit.

Safety factor: 5:1

WLL (metric) tonnes	A in	B mmin	C mmin	D mmin	H mmin	K mmin	Lin	Weight lb
0.75	0.59	1.26	0.47	0.39	0.87	4.06	4.96	1.1
1	0.71	1.57	0.63	0.43	1.02	4.41	5.67	1.76
3	0.91	2.01	0.91	0.63	1.22	6.26	7.99	4.41
5	1.26	2.52	1.22	0.87	1.46	7.87	10.31	8.82
8.5	1.46	2.99	1.38	0.98	1.97	9.53	12.28	14.77
10	1.65	4.02	1.81	1.5	2.09	12.48	16.06	40.12
15	1.89	4.25	1.81	1.5	2.2	12.48	16.06	46.3
25	2.44	5.2	2.4	2.01	2.72	14.72	19.49	80.47

Blueprint

