

Screw Pin Sling Shackle Crosby S-253

Product information



The Crosby S-253 top sling is designed to connect slings to steel fittings.

Meets or exceeds all requirements of ASME B30.26 including identification, ductility, design factor, proof load and temperature requirements. Importantly, these shackles meet other critical performance requirements including fatigue life, impact properties and material traceability, not addressed by ASME B30.26.

... [Read more](#)


Material: All alloy construction.

Marking: CE-marked, Each shackle has a Product Identification Code (PIC) for material traceability along with a Working Load Limit and the name Crosby forged into it.

Safety factor: 5:1

Screw Pin Sling Shackle Crosby S-253

Blueprint



Technical data

Part code	WLL (metric) tonnes	Eye width mm	A in	B in	C in	D, in	E in	G, in	K in	L in	Mmm in	Nmm in	Pmm in	Rmm in	Weight lb
11.341020575	3.25	25	0.88	0.62	1.38	0.75	1.5	3.39	1.5	0.75	2.7	3.23	0.44	1	1.41
11.341020584	6.5	35	1.25	0.75	1.75	0.88	1.88	4.13	1.81	1	3.39	4.02	0.5	1.19	2.2
11.341020593	8.75	50	1.38	0.88	2.24	1	2.81	5.51	2.09	1.12	4.17	4.49	0.5	1.44	3.79
11.341020602	12.5	75	1.62	1.12	3.25	1.25	3.05	6.34	2.62	1.38	5.63	5.59	0.62	1.81	7.3
11.341020611	20.5	100	2.13	1.38	4.49	1.5	5.24	9.45	3.11	1.75	7.52	6.89	0.75	2.13	15.19
11.341020620	35	125	2.5	1.75	5.51	2.01	6.34	11.5	4.17	2.24	9.17	8.66	1	2.87	30.86
11.341020629	50	150	2.99	2.13	6.5	2.24	7.72	13.74	4.76	2.76	10.98	10.24	1.22	3.19	52.03