

Wire Rope Clip Crosby G-450

Product information



Based on the catalog breaking strength of wire rope, Crosby wire rope clips have an efficiency rating of 80% for 3 mm through 22 mm sizes, and 90% for sizes 24 mm through 90 mm.

... [Read more](#)

Features: Wire clips to secure and form a temporary termination on site.

Material: Steel

Marking: According to standard, ID code and Manufacturer's symbol


Finish: Galvanised

Standard: EN 13411-5

Note: All sizes except 68-72 mm and 85-90 mm meet the performance requirements of EN13411.

Wire Rope Clip Crosby G-450

Blueprint



Wire Rope Clip Crosby G-450

Technical data

Part code	Rope diameter inch	Rope Ø range mm	A in	B in	C in	D, in	E in	F in	G, in	H, in	Weight lb
121100400120	1/8	3-4	0.22	0.72	0.44	0.47	0.41	0.38	0.81	0.94	0.06
121100500120	3/16	5	0.25	0.97	0.56	0.59	0.5	0.44	0.94	1.16	0.1
121100700120	1/4	6-7	0.31	1.03	0.5	0.75	0.66	0.56	1.19	1.44	0.19
121100800120	5/16	8	0.38	1.38	0.75	0.88	0.72	0.69	1.31	1.69	0.28
121101000120	3/8	9-10	0.44	1.5	0.75	1	0.91	0.75	1.63	1.94	0.48
121101100120	-	11	0.5	1.88	1	1.19	1.03	0.88	1.81	2.28	0.78
121101300120	7/16 - 1/2	11-13	0.02	0.07	0.04	0.05	0.04	0.03	0.08	0.09	1.76
121101500120	-	14-15	0.56	2.24	1.25	1.31	1.22	0.94	2.07	2.5	1.09
121101600120	9/16 - 5/8	16	0.02	0.09	0.05	0.05	0.05	0.04	0.08	0.1	2.43
121102000120	3/4	18-20	0.62	2.76	1.44	1.5	1.41	1.06	2.24	2.83	1.41
121102200120	7/8	22	0.75	3.11	1.62	1.75	1.59	1.25	2.44	3.17	2.12
121102600120	1	24-26	0.75	3.5	1.81	1.88	1.78	1.25	2.64	3.46	2.51
121103000120	1-1/8	28-30	0.75	3.88	2.01	2.01	1.91	1.25	2.81	3.58	2.82
121103400120	1-1/4	32-34	0.88	4.25	2.13	2.34	2.19	1.44	3.13	4.13	4.39
121103600120	1-3/8	36	0.88	4.65	2.3	2.34	2.3	1.44	3.13	4.17	4.41
121103800120	1-1/2	38	0.88	4.92	2.38	2.62	2.44	1.44	3.41	4.45	5.45
121104200120	1-5/8	41-42	1	5.31	2.62	2.76	2.66	1.63	3.62	4.76	7.03
121104600120	1-3/4	44-46	1.13	5.75	2.76	3.05	2.93	1.81	3.82	5.28	9.35
121105200120	2	48-52	1.25	6.46	2.99	3.39	3.03	2.01	4.45	5.87	13.01
121105800120	2-1/4	56-58	1.25	7.13	3.19	3.88	3.19	2.01	4.49	6.38	16.01
121106500120	2-1/2	62-65	1.25	7.68	3.44	4.13	3.68	2.01	4.69	6.61	19
121107200120	2-3/4	68-72	1.25	8.31	3.56	4.37	4.88	2.01	5	6.89	22.99
121107800120	3	75-78	1.5	9.17	3.88	4.76	4.69	2.38	5.87	7.64	31
121109000120	3-1/2	85-90	1.5	10.75	4.49	5.51	5.98	2.38	6.18	8.39	39.99