Industrial Rigging & Supply | Lifting Solutions Group Axel Johnson International

Clevis Self Locking Hook X-026

Product information



- At least 25% greater WLL than traditional Grade 8 products.
- Manufactured in accordance with EN 1677-3 and ASME B30.26.
- Proof Load tested at 2.5 times the WLL with certification for each batch manufactured. Fatigue rated to 20,000 cycles at 1.5 times the WLL.
- Tempering temperature minimum 400°C.
- Magnaflux crack detection is performed 100% on each batch.

When fitting G10 components are added to G8 chain, the sling is rated at G8 WLL
... *Read more*

Material: Quenched and tempered alloy steel.
Marking: According to standard, Size, grade, manufacturer ID, traceability.
Temperature range: -40ºC up to +200°C (without reduction in WLL).
Finish: Blue painted.
Standard: EN 1677-3


Safety factor: 4:1
Grade: 10

© November 2026 - All Rights Reserved

Industrial Rigging & Supply | Lifting Solutions Group Axel Johnson International

Clevis Self Locking Hook X-026

Blueprint



Technical data

Part code	Chain diameter in	WLL lb	EWL mm	A in	H in	K in	P in	T in	Weight lb
402300140730	7/32	3,200	93	0.28	0.75	3.7	1.1	0.59	0.88
402300250730	1/4-5/16	5,700	119	0.35	0.94	4.69	1.34	0.79	1.98
402300400730	3/8	8,800	142	0.43	1.18	5.59	1.73	1.02	3.09
402300670730	1/2	15,000	178	0.59	1.54	7.01	2.05	1.18	6.61
402301000730	5/8	22,600	213	0.71	1.93	8.39	2.36	1.42	11.02
402301600730	3/4	35,300	244	0.98	2.56	9.88	2.76	2.09	24.25
402301900730	7/8	42,700	273	0.94	2.48	10.75	3.15	1.93	29.76

© November 2026 - All Rights Reserved