

## Connecting Link X-015 Grade 10

---

### Product information



- At least 25% greater WLL than traditional Grade 8 products.
- Proof Load tested at 2.5 times the WLL with certification for each batch manufactured.
- Fatigue rated to 20,000 cycles at 1.5 times the WLL.
- Suitable for use with both Grade 8 and Grade 10 chain.

When fitting G10 components are added to G8 chain, the sling is rated at G8 WLL  
... [Read more](#)

---

**Material:** Quenched and Tempered Alloy Steel.

**Marking:** According to standard, Type, manufacturer ID, traceability.

**Temperature range:** -40° up to +200°C (without reduction in WLL).

**Finish:** Blue painted.


**Standard:** EN 1677-1

**Safety factor:** 4:1

**Grade:** 10

## Connecting Link X-015 Grade 10

### Blueprint



### Technical data

Part code	Chain diameter in	WLL	EWL mm	A in	B in	D, in	K in	Weight lb
402200140190	7/32	3,200	45	0.59	0.67	0.28	1.77	0.18
402200250190	1/4-5/16	5,700	59	0.71	0.91	0.35	2.32	0.44
402200400190	3/8	8,800	69	0.98	1.06	0.43	2.72	0.66
402200670190	1/2	15,000	92	1.18	1.46	0.63	3.62	1.54
402201000190	5/8	22,600	101	1.42	1.54	0.75	3.98	2.65
402201600190	3/4	35,300	122	1.65	1.81	0.91	4.8	4.63
402201900190	7/8	42,700	152	1.93	2.32	0.94	5.98	7.72
402202650190	1	59,700	162	2.17	2.44	1.18	6.38	10.58
402204000190	1-1/4	90,400	203	2.72	3.11	1.42	7.99	19.84