



## Connecting Link X-015 Grade 10

### Product information

- At least 25% greater WLL than traditional Grade 8 products.
- Proof Load tested at 2.5 times the WLL with certification for each batch manufactured.
- Fatigue rated to 20,000 cycles at 1.5 times the WLL.
- Suitable for use with both Grade 8 and Grade 10 chain.

When fitting G10 components are added to G8 chain, the sling is rated at G8 WLL.

**Marking:** According to standard

**Standard:** EN 1677-1

**Safety factor:** 4:1

**Grade:** 10

Part code	Chain diameter in	WLL	Chain diameter mm	WLL (metric) tonnes	EWL mm	A mm	B mm	D mm	K mm	Weight kg
402200140190	7/32	3,200	6	1.4	45	15	17	7	45	0.08
402200250190	1/4-5/16	5,700	7-8	2.5	59	18	23	9	59	0.2
402200400190	3/8	8,800	10	4	69	25	27	11	69	0.3
402200670190	1/2	15,000	13	6.7	92	30	37	16	92	0.7
402201000190	5/8	22,600	16	10	101	36	39	19	101	1.2
402201600190	3/4	35,300	20	16	122	42	46	23	122	2.1
402201900190	7/8	42,700	22	19	152	49	59	24	152	3.5
402202650190	1	59,700	26	26.5	162	55	62	30	162	4.8
402204000190	1-1/4	90,400	32	40	203	69	79	36	203	9

## Blueprint

