Industrial Rigging & Supply | Lifting Solutions Group Axel Johnson International

Clevis Sling Hook X-043/S Grade 10

Product information



At least 25% greater WLL than traditional Grade 8 products.
Proof Load tested at 2.5 times the WLL with certification for each batch manufactured. Fatigue rated to 20,000 cycles at 1.5 times the WLL.
Tempering temperature minimum 400°C.
Magnaflux crack detection is performed 100% on each batch.

... *Read more*

Material: Quenched and Tempered Alloy Steel.
Marking: According to standard, Size, grade, manufacturer ID, traceability.
Temperature range: -40ºC up to +200°C (without reduction in WLL).
Finish: Blue painted.
Standard: EN 1677-2

Safety factor: 4:1
Grade: 10


Industrial Rigging & Supply
info@industrialrigging.ca
+1 (519) 624-9697

© November 2026 - All Rights Reserved

Industrial Rigging & Supply | Lifting Solutions Group Axel Johnson International

Clevis Sling Hook X-043/S Grade 10

Blueprint



Technical data

Part code	Chain diameter in	WLL lb	EWL mm	A in	H in	K in	P1 in	T in	Weight lb
402300140700	7/32	3,200	79	0.28	0.71	3.11	0.91	0.59	0.66
402300250700	1/4-5/16	5,700	98	0.35	0.87	3.86	1.06	0.71	1.32
402300400700	3/8	8,800	122	0.47	1.18	4.8	1.34	0.94	2.43
402300670700	1/2	15,000	147	0.59	1.46	5.79	1.73	1.18	5.07
402301000700	5/8	22,600	166	0.67	1.61	6.54	1.89	1.54	8.38
402301600700	3/4	35,300	207	0.94	2.52	8.15	2.24	1.89	19.18
402301900700	7/8	42,700	217	0.98	2.4	8.54	2.87	2.05	20.94

Industrial Rigging & Supply
info@industrialrigging.ca
+1 (519) 624-9697

© November 2026 - All Rights Reserved