Industrial Rigging & Supply | Lifting Solutions Group
Axel Johnson International

Clevis Grab Hook X-042

Product information



- At least 25% greater WLL than traditional Grade 8 products.
- Testing according to DIN PAS 1061 and ASTM A952/A 952M.
- Proof Load tested at 2.5 times the WLL with certification for each batch manufactured.
- Fatigue rated to 20,000 cycles at 1.5 times the WLL.
- Enables full WLL while in use, thanks to supporting wings which prevent chain link deformation.

When fitting G10 components are added to G8 chain, the sling is rated at G8 WLL
... *Read more*

Material: Quenched and Tempered Alloy Steel
Marking: According to standard, Size, grade, manufacturer ID, traceability.
Temperature range: -40ºC up to +200°C (without reduction in WLL).
Standard: EN 1677-1
Warning: Not for use with Omega Link

Safety factor: 4:1
Grade: 10

© November 2026 - All Rights Reserved

Industrial Rigging & Supply | Lifting Solutions Group Axel Johnson International

Clevis Grab Hook X-042

Blueprint



Technical data

Part code	Chain diameter in	WLL lb	EWL mm	A in	F in	H in	K in	L in	P in	Weight lb
402300140810	7/32	3,200	47	0.28	0.98	0.71	1.85	3.11	0.31	0.44
402300250810	1/4-5/16	5,700	54	0.39	1.18	0.87	2.13	3.66	0.39	0.88
402300400810	3/8	8,800	77	0.43	1.61	1.14	3.03	5.04	0.51	1.76
402300670810	1/2	15,000	99	0.59	2.05	1.5	3.9	6.5	0.67	3.53
402301000810	5/8	22,600	114	0.71	2.24	1.77	4.49	7.68	0.83	5.95
402301600810	3/4	35,300	130	0.87	2.87	2.05	5.12	8.74	0.91	10.58
402301900810	7/8	42,700	139	0.94	2.76	2.2	5.47	9.72	1.02	14.11

© November 2026 - All Rights Reserved