

Horizontal Lifting Clamp IPHGUZ

Product information



Horizontal Lifting Clamp IPHGUZ for horizontal transfer with pretension system.

Features:

- Available in capacities of 1.5 through 4.5 metric tons
- Wide variety of jaw openings available: 0 to 40mm
- Welded alloy steel body for strength and smaller size. Forged alloy components, where required
- Individually Proof Tested to 2 times the Working Load Limit with certification
- User manual with test certificate is included with each clamp
- Maintenance and repair kits are available

... [Read more](#)

Material: Alloy steel


Marking: According to standard, WLL, Logo, Jaw opening, Serial number

Temperature range: -40 °C (-40 °F) up to +100 °C (+212 °F)

Standard: EN 13155

Horizontal Lifting Clamp IPHGUZ

Blueprint



Technical data

WLL (metric) tonnes	Jaw width in	A in	B in	C in	D, in	E in	F in	G, in	J in	K in	Weight lb
1.5	0-0.98	0-0.98	4.33	9.13	11.3	2.76	5.47	3.54	0.79	0.63	19.84
3	0-1.57	0-1.57	4.69	9.96	13.7	2.95	6.89	4.72	0.98	1.57	43.87
4.5	0-1.57	0-1.57	4.69	11.85	14.57	3.15	6.89	6.1	1.18	1.73	66.14