

Horizontal Lifting Clamp IPHOZ

Product information



The IPHOZ horizontal lifting clamp is to be used for lifting and transferring, in the horizontal position, of thin sheet and other materials that will sag or bend when lifted. These clamps must be used in pairs or more.

Features:

- Available in capacities of 0.75 through 15 metric tons
- Wide variety of jaw openings available: 0 to 60mm
- Welded alloy steel body for strength and smaller size. Forged alloy components, where required
- Individually Proof Tested to 2 times the Working Load Limit with certification
- User manual with test certificate is included with each clamp
- Maintenance and repair kits are available
- All sizes are RFID EQUIPPED

... [Read more](#)

Material: Alloy steel

Marking: According to standard, CE-marked, WLL, Logo, Jaw opening, Serial number


Temperature range: -40°C up to +100°C

Standard: EN 13155

Warning: Only to be used in pairs.

Horizontal Lifting Clamp IPHOZ

Blueprint



Technical data

Part code	WLL (metric) tonnes	Jaw width in	Model	A in	B in	C in	E in	F in	G, in	H, in	J in	K in	L in	Weight lb
16.012705401	0.75	0-1.18	0.75-IPHOZ	0-1.18	3.7	0.63	0.63	2.76	4.65	3.19	0.47	1.22	0.47	6.61
16.012705402	1.5	0-1.77	1.5-IPHOZ	0-1.77	5.24	0.63	0.87	4.92	7.56	3.94	0.63	1.42	0.47	12.13
16.012705403	3	0-1.77	3-IPHOZ	0-1.77	5.39	0.79	1.02	4.92	7.87	4.72	0.79	1.89	0.39	17.64
16.012705404	4.5	0-1.77	4.5-IPHOZ	0-1.77	5.43	0.98	1.18	4.96	8.66	4.72	0.79	1.97	0.39	20.94
16.012705405	6	0-2.36	6-IPHOZ	0-2.36	6.73	1.18	1.42	5.31	9.25	5.12	0.79	2.2	0.79	34.17
16.012705406	9	0-2.36	9-IPHOZ	0-2.36	8.31	1.18	1.69	6.54	10.87	6.3	0.98	2.44	0.79	55.12
16.012705407	12	0-2.36	12-IPHOZ	0-2.36	8.54	1.57	1.85	6.61	11.57	7.48	0.98	2.44	0.75	63.93
16.012705408	15	0-2.36	15-IPHOZ	0-2.36	-	-	-	-	-	-	-	-	-	83.78