



Swivel Hoist Ring Crosby, HR-1000 UNC

Product information

- Forged bail provides the following:
 - Easily readable raised lettering showing the name Crosby or "CG" and PIC for material traceability.
 - Greater durability providing the increased "Toughness" desired in potentially abusive field conditions.
 - Larger opening than standard hoist ring bail.
- Top washer is color-coded for easy identification (Red for UNC threads and Silver for Metric threads)
- The Working Load Limit and recommended torque value are permanently stamped into each washer.
- Individually Proof Tested to 2-1/2 times Working Load Limit.
- Available in both UNC thread and Metric thread style.
- UNC bolt specification is an alloy socket head cap screw to ASTM A 574. Metric bolt specification is a Grade 12.9 alloy socket head cap screw to DIN 912.
- BOLT SIZE IDENTIFICATION: The size of the bolt will be stated as in the drawing. Illustration shows meaning of each dimension given.

Safety factor: 5:1

Part code	WLL (metric) tonnes	Thread Inch	B in	C in	D, in	E in	F in	G, in	H, in	Weight lb
-	1.134	1/2 - 13 x 2.75	1.19	6.26	1.96	1.25	0.62	4.21	2.5	3.06
-	2.268	3/4 - 10 x 2.50	0.94	6.26	1.96	1.25	0.62	4.21	2.5	3.24
07.111068050	4.536	1 - 8 x 3.50	0.05	0.34	0.12	0.06	0.04	0.25	0.13	10.49
07.111068058	6.804	1-1/4 - 7 x 5.00	0.08	0.44	0.15	0.08	0.05	0.31	0.16	21.89

Blueprint

