

Eye Grip Safe Locking Hook X-950

Product information



- At least 25% greater WLL than traditional Grade 8 products.
- Proof Load tested at 2.5 times the WLL with certification for each batch manufactured. Fatigue rated to 20,000 cycles at 1.5 times the WLL.
- Magnaflux crack detection is performed 100% on each batch.
- Avoid finger injury by the grip design.

When fitting G10 components are added to G8 chain, the sling is rated at G8 WLL
... [Read more](#)

Material: Quenched and Tempered Alloy Steel.

Marking: According to standard, Size, grade, manufacturer ID, traceability.

Temperature range: -40°C up to +200°C (without reduction in WLL).

Finish: Blue painted.


Standard: EN 1677-3

Safety factor: 4:1

Grade: 10

Eye Grip Safe Locking Hook X-950

Blueprint



Technical data

Part code	Chain diameter in	WLL	EWL mm	A in	D, in	H, in	K in	Omm in	Pmm in	T in	Wmm in	Weight lb
402300400850	3/8	8,800	175	1.3	0.51	1.22	6.93	1.93	2.8	1.06	5.39	4.19
402300670850	1/2	15,000	227	1.57	0.63	1.54	8.9	2.52	3.15	1.34	6.85	8.82
402301000850	5/8	22,600	277	1.97	0.83	1.85	10.91	3.07	4.49	1.54	8.35	13.89
402301600850	3/4	35,300	329	2.44	0.91	2.17	12.95	3.62	5	2.13	9.88	27.12
402302000850	7/8	42,700	350	2.76	0.94	2.32	13.78	3.86	5.94	2.2	10.16	30.86