

Swivel Grip Safe Locking Hook X-952N

Product information



Proof Load tested at 2.5 times the WLL with certification for each batch manufactured. Fatigue rated to 20,000 cycles at 1.5 times the WLL. Magnaflux crack detection is performed 100% on each batch. Built with ball bearing and enables full swivel feature under load.

When fitting G10 components are added to G8 chain, the sling is rated at GR WLL
... [Read more](#)

Material: Quenched and Tempered Alloy Steel.

Marking: According to standard, Size, grade, manufacturer ID, traceability.

Temperature range: -40°C up to +200°C (without reduction in WLL).


Standard: EN 1677-1

Safety factor: 4:1

Grade: 10

Swivel Grip Safe Locking Hook X-952N

Blueprint



Technical data

Part code	Chain diameter in	WLL	EWL mm	A in	B in	D in	H, in	K in	Omm in	Pmm in	T in	Wmm in	Weight lb
420500400960	3/8	8,800	225	1.61	1.38	0.63	1.22	8.9	1.93	2.8	1.06	5.39	5.29
420500670960	1/2	15,000	285	1.81	1.73	0.83	1.54	11.14	2.52	3.15	1.34	6.85	11.46
420501000960	5/8	22,600	345	2.4	1.97	0.91	1.85	13.66	3.07	4.49	1.54	8.35	18.52
420501600960	3/4	35,300	433	2.91	3.23	0.98	2.17	17.05	3.62	5	2.13	9.88	31.97
420501900960	7/8	42,700	475	3.82	3.78	1.3	2.32	18.74	3.86	5.94	2.2	10.16	44.97