

Swivel Bearing Hoist Hook X-175N

Product information



- 20,000 cycle fatigue rated to 1.5 times of 4:1 WLL
- All swivel hoist hooks are 100% magnaflux crack detected.
- Ball bearing performs fully swivel under load.

... [Read more](#)

Material: Alloy steel - quenched and tempered

Marking: CE-marked, Batch number, grade, chain size


Finish: Blue painted.

Safety factor: 4:1

Grade: 10

Swivel Bearing Hoist Hook X-175N

Blueprint



Technical data

Part code	Code	Chain diameter in	WLL (metric) tonnes	A in	B in	C in	D, in	G, in	H, in	K in	L in	Pmm in	P1 mm in	T in	Weight lb
420500100920	AA mm	3/16	1	1.26	0.91	0.98	0.47	2.87	0.75	4.92	6.14	0.94	0.87	0.67	1.32
420500140920	BB mm	7/32	1.4	1.26	0.91	0.98	0.47	3.19	0.91	5.16	6.5	0.94	0.75	0.67	1.54
420500250920	CC	1/4	2.5	1.42	1.14	1.02	0.51	3.54	1.06	5.71	7.24	0.94	0.79	0.87	2.2
420500400920	DD	3/8	4	1.61	1.38	1.14	0.63	4.02	1.14	6.77	8.54	1.1	0.98	0.94	3.53
420500670920	EE	1/2	6.7	1.81	1.73	1.5	0.83	4.8	1.5	8.58	10.91	1.38	1.22	1.22	7.28
420501000920	FF	5/8	10	2.4	1.97	1.93	0.91	6.3	1.89	10.28	13.07	1.69	1.54	1.38	12.35
420501600920	GG	3/4	16	2.91	3.23	2.44	0.98	7.72	2.2	12.87	16.14	2.4	2.24	1.85	20.94
420501900920	HH	7/8	19	3.82	3.78	2.56	1.3	8.7	2.52	14.65	18.54	2.83	2.44	2.2	35.27
420502650920	JJ	1	26.5	4.84	4.57	2.8	2.01	10.91	2.99	18.46	23.58	3.39	3.19	2.68	73.85
420504000920	KK	1 1/4	40	4.84	4.57	3.43	2.01	13.9	3.66	19.8	25.63	3.5	3.27	2.99	99.21