

## Clevis Slip Hook Crosby A-331

### Product information



- All pins are alloy steel – Quenched & Tempered.
- Not suitable for use with Grade 80 chain and chain slings used in overhead lifting. For slings or lifting chains, Grade 80 or 100 alloy components are recommended.

... [Read more](#)


**Material:** Forged alloy steel – Quenched & Tempered.

**Safety factor:** 4:1

**Grade:** 8

# Clevis Slip Hook Crosby A-331

## Blueprint



## Technical data

Part code	Chain diameter in	WLL lb	A in	B in	C in	D in	E in	F in	G, in	H, in	K in	L in	Nmm in	Pmm in	Rmm in	T in	Weight lb
401300131610	1/4	2,750	1.06	0.32	0.29	2.76	0.94	1.19	0.81	0.88	0.5	3.94	2.13	0.31	2.58	0.72	0.55
401300201610	5/16	4,300	1.22	0.43	0.34	3.05	1.06	1.25	0.94	1	0.56	4.53	2.24	0.38	2.87	0.97	0.79
401300241610	3/8	5,250	1.38	0.45	0.44	3.62	1.31	1.5	1.13	1.19	0.66	5.16	2.56	0.44	3.25	1.06	1.21
401300321610	7/16	7,000	1.73	0.59	0.6	4.33	1.56	1.81	1.38	1.44	0.81	5.98	3.05	0.56	3.7	1.19	2.05
401300411610	1/2	9,000	1.88	0.57	0.53	4.8	1.69	1.94	1.56	1.63	0.91	6.54	3.44	0.63	4.02	1.31	2.76
401300611610	5/8	13,500	2.3	0.71	0.71	5.63	2.01	2.38	1.81	1.94	1.09	7.87	4.02	0.75	4.92	1.56	4.74
401300871610	3/4	19,250	3.19	1.18	1.29	7.36	2.5	3	2.38	2.5	1.44	10.04	5.08	1	6.1	2.09	11.29