

## Weld-On Load Ring 8-082



### Product information

- Pivots 180°, designed minimizes head room.
- Load rated parts are 100% magnaflux crack detected.
- The two points of attachment facilitate an even and optimal force distribution into the work piece and thus, usage of thinner base plates is possible.
- The welding block is forged out of material with excellent welding properties.
- Low profile design with high strength.
- The ring is stowable thus avoiding the hazards of tripping and snagging.

**Material:** Forged alloy steel, quenched and tempered.

**Marking:** According to standard, CE-marked

**Finish:** Painted.

**Standard:** EN 1677-1

**Safety factor:** 4:1

Part code	WLL (metric) tonnes	A in	B in	C in	D, in	E in	F in	L in	Mmm in	HV mm in	a in	Weight lb
11.428-082-04	4	2.6	0.55	1.18	1.89	2.56	2.76	5.31	2.99	0.2	0.12	1.32
11.428-082-06	6.7	3.35	0.79	1.54	2.36	3.5	3.58	6.73	3.86	0.2	0.12	3.31
11.428-082-10	10	3.74	0.83	1.81	2.56	3.94	3.94	7.72	4.17	0.28	0.16	5.29
11.428-082-16	16	5	1.18	2.24	3.54	5.12	5.35	10.35	5.87	0.31	0.16	12.13
11.428-082-30	31.5	7.01	1.65	2.95	5.12	6.3	7.68	14.76	8.39	0.59	0.16	34.83



# Blueprint

