

## Horizontal Lifting Clamp IPH10E/IPH10JE



### Product information

For horizontal lifting and transfer.

#### Features:

- Available in capacities of 2.0 thru 12 metric tons.
- Wide variety of jaw openings available: 0 to 120mm.
- Equipped with handle for easy placement.
- Individually Proof Tested to 2 times the Working Load Limit with certification.

**Material:** Alloy steel

**Marking:** According to standard, CE-marked, WLL, Logo, Jaw opening, Serial number

**Temperature range:** -40°C up to +100°C

**Standard:** EN 13155

Code	WLL (metric) tonnes	Jaw width in	B in	C in	E in	F in	G, in	H, in	J in	K in	L in	Weight lb
IPH10E	2	0-2.36	4.61	0.63	0.87	4.29	10.08	4.33	0.79	1.57	0.35	12.13
IPH10E	3	0-2.36	4.61	0.79	1.02	4.29	10.47	4.72	0.79	1.89	0.43	16.53
IPH10E	4.5	0-2.36	5.2	0.98	1.18	4.09	11.02	5.12	0.79	1.89	0.47	23.15
IPH10E	6	0-2.36	5.63	0.98	1.42	4.84	12.6	5.12	0.79	1.89	0.55	28.66
IPH10E	9	0-2.36	6.18	1.18	1.69	5.24	12.99	5.51	0.98	2.44	0.63	40.79
IPH10E	12	0-2.36	6.77	1.18	1.85	5.55	13.9	5.91	0.98	2.44	0.67	47.4

# Blueprint

