



Swivel Hoist Ring Crosby, HR 1000

Product information

Swivel hoist ring HR-1000 from Crosby

- Forged bail provides the following:
 - Easily readable raised lettering showing the name Crosby or "CG" and PIC for material traceability.
 - Greater durability providing the increased "Toughness" desired in potentially abusive field conditions.
 - Larger opening than standard hoist ring bail.
- Top washer is color-coded for easy identification (Red for UNC threads and Silver for Metric threads)
- The Working Load Limit and recommended torque value are permanently stamped into each washer.
- Individually Proof Tested to 2-1/2 times Working Load Limit.
- UNC bolt specification is an alloy socket head cap screw to ASTM A 574. Metric bolt specification is a Grade 12.9 alloy socket head cap screw to DIN 912.
- BOLT SIZE IDENTIFICATION: The size of the bolt will be stated as in the drawing. Illustration shows meaning of each dimension given.

Safety factor: 4:1

WLL (metric tonnes)	A mm	B in	C in	D, in	E in	F in	G, in	H, in	Weight lb
0.5	M8 x 1.25 x 40	0.6	3.69	0.97	0.62	0.44	2.27	1.38	0.66
0.55	M10 X 1.5 X 40	0.6	3.69	0.97	0.62	0.44	2.27	1.38	0.66
1.3	M12 x 1.75 x 55	0.61	6.38	1.96	1.25	0.75	4.21	2.5	3.31
2.4	M16 X 2.00 X 65	1	6.38	1.96	1.25	0.75	4.21	2.5	3.31
2.7	M20 x 2.50 x 70	1.2	6.38	1.96	1.25	0.75	4.21	2.5	3.53
3.75	M20 X 2.50 X 80	1	8.66	2.96	1.63	1	6.26	3.25	10.14
5.25	M24 x 3.00 x 90	1.39	8.66	2.96	1.63	1	6.26	3.25	10.58
8.75	M30 x 3.50 x 140	2.61	11.22	3.71	2	1.25	7.83	4.02	21.38
13.75	M36 x 4.00 x 130	2.21	11.22	3.71	2	1.25	7.83	4.02	22.49

Blueprint

