



Clevis Sling Hook Green Pin® CSCI, Stainless Steel

Product information

The Green Pin® Stainless Steel Sling Hook CL is a grade 5 stainless steel clevis sling hook. The non-corrosive nature of stainless steel makes it the perfect choice for use in industries such as foods, nuclear and sailing. The sling hook can be used for general lifting applications. It can be quickly connected to the load lifting points thanks to its easy operating latch, which guarantees full safety. To connect simply push the latch, connect the hook to the lifting point, and release the latch. The forged latch guarantees a longer lifespan. It strongly limits the risk that the operator uses the hook without latch. The latch is fitted with a stainless steel spring and a sturdy pin.

Certification on request: 2.1, 2.2, 3.1

Material: AISI 316L

Temperature range: -40°C up to +200°C

Finish: Polished

Safety factor: 4:1

Grade: 5

| Part code | Chain diameter in | WLL (metric) tonnes | a in | b mm in | c in | dmm in | e mm in | f mm in | g mm in | h mm in | i mm in | Weight lb |
|--------------|----------------------|------------------------|------|---------|------|--------|---------|---------|---------|---------|---------|--------------|
| 400300070130 | 7/32 | 0.7 | 2.91 | 0.28 | 1.02 | 0.59 | 0.79 | 1.1 | 2.83 | 4.25 | 0.31 | 0.64 |
| 400300120130 | 1/4-5/16 | 1.2 | 3.74 | 0.37 | 1.18 | 0.79 | 0.94 | 1.26 | 3.43 | 5.35 | 0.35 | 1.21 |
| 400300160130 | 3/8 | 1.6 | 4.45 | 0.45 | 1.3 | 0.94 | 1.14 | 1.65 | 4.17 | 6.46 | 0.51 | 2.43 |
| 400300270130 | 1/2 | 2.7 | 5.47 | 0.59 | 1.46 | 1.26 | 1.54 | 2.13 | 5.24 | 8.19 | 0.63 | 4.1 |

Blueprint

