

Fishing Bow Shackle FP Green Pin® G-4169

Product information



The Green Pin® Fishing Bow Shackle FP is a bow shackle with a square sunken hole screw pin (flush pin). The Green Pin® Fishing Bow Shackle FP contains no protruding parts so it does not damage or get caught in fishing nets. Another important feature is that the chamber in the shackle eye hides the screw thread and reduces wear of rope. Galvanization of the bow shackle ensures its long-term durability. The Green Pin® Fishing Bow Shackle FP is suitable for both one-leg and multi-leg systems and can be assembled with the help of the Green Pin® Sunken Hole Key. The shackle is available in a range with a working load limit from 2 up to 17 ton.

Certification on request: 2.1, 2.2, 3.1, MTCa

[... Read more](#)

Material: Bow and pin high tensile steel, quenched and tempered.

Marking: According to standard, CE-marked

Finish: Hot dipped galvanized

Standard: EN 13889


Note: Key for unscrewing the pin sold separately.

Safety factor: 6:1

Grade: 6

Fishing Bow Shackle FP Green Pin® G-4169

Blueprint



Technical data

Part code	WLL (metric) tonnes	a in	b mm in	c in	d mm in	e mm in	f mm in	g mm in	h mm in	i mm in	j mm in	k mm in	Weight lb
420100200650	2	0.53	0.63	1.34	0.51	0.87	2.01	1.26	3.5	2.01	2.28	0.43	0.68
420100330650	3.25	0.63	0.75	1.57	0.63	1.06	2.52	1.69	4.33	2.48	2.95	0.43	1.23
420100480650	4.75	0.75	0.87	1.81	0.75	1.22	2.99	2.01	5.08	2.91	3.5	0.43	2.16
420100650650	6.5	0.87	0.98	2.05	0.87	1.42	3.27	2.28	5.67	3.35	4.02	0.51	3.22
420100850650	8.5	0.98	1.1	2.32	0.98	1.69	3.74	2.68	6.46	3.9	4.65	0.51	4.81
420100950650	9.5	1.1	1.26	2.6	1.1	1.85	4.25	2.95	7.28	4.33	5.16	0.67	6.75
420101200650	12	1.26	1.38	2.83	1.26	2.01	4.53	3.27	7.91	4.8	5.79	0.67	9.35
420101350650	13.5	1.38	1.5	3.15	1.38	2.24	5.24	3.62	8.94	5.31	6.38	0.67	12.32
420101700650	17	1.5	1.65	3.46	1.5	2.36	5.75	3.9	9.8	5.71	6.89	0.67	16.25