



Sling Hook Green Pin® CSEI, Stainless Steel

Product information

The Green Pin® Stainless Steel Sling Hook SE is a grade 5 stainless steel swivel sling hook with eye. The non-corrosive nature of stainless steel makes it the perfect choice for use in industries such as foods, nuclear and sailing. The sling hook can be used for general lifting applications. It can be quickly connected to the load lifting points thanks to its easy operating latch, which guarantees full safety. To connect simply push the latch, connect the hook to the lifting point, and release the latch. The forged latch guarantees a longer lifespan. It strongly limits the risk that the operator uses the hook without latch. The latch is fitted with a stainless steel spring and a sturdy pin. The large eye, designed with a flat enables an easy assembly on anti-rotating wire rope slings (with an omega link or with thimbles). These hooks are fitted with a stainless steel washer. The eye of the hook can also be connected to grade 5 chain with a connecting link or to a webbing with a web sling connector. The Green Pin® Stainless Steel Sling Hook SE is available in a range to suit 6 mm up to 13 mm grade 5 chain.

Certification on request: 2.1, 2.2, 3.1

Material: AISI 316L

Temperature range: -40°C up to +200°C

Finish: Polished

Safety factor: 4:1

Grade: 5

Part code	Chain diameter in	WLL (metric) tonnes	a in	b mm in	c in	dmm in	e mm in	f mm in	g mm in	h mm in	i mm in	j mm in	Weight lb
400300070120	7/32	0.7	3.94	1.3	1.26	1.02	0.59	0.79	2.83	6.46	0.43	0.24	1.19
400300120120	1/4-5/16	1.2	4.96	1.57	1.46	1.18	0.79	0.98	3.43	8.03	0.51	0.31	1.7
400300160120	3/8	1.6	6.22	1.85	1.89	1.3	0.94	1.14	4.17	9.84	0.63	0.43	4.23
400300270120	1/2	2.7	7.44	2.32	2.28	1.46	1.26	1.54	5.24	12.13	0.83	0.53	7.47

Blueprint

