



## Sling Hook Green Pin® CSOI, Stainless Steel

### Product information

The Green Pin® Stainless Steel Sling Hook E is a grade 5 stainless steel eye sling hook. The non-corrosive nature of stainless steel makes it the perfect choice for use in industries such as foods, nuclear and sailing. The sling hook can be used for general lifting applications. It can be quickly connected to the load lifting points thanks to its easy operating latch, which guarantees full safety. To connect simply push the latch, connect the hook to the lifting point, and release the latch. The forged latch guarantees a longer lifespan. It strongly limits the risk that the operator uses the hook without latch. The latch is fitted with a stainless steel spring and a sturdy pin. The eye of the hook can be connected to grade 5 chain with a connecting link or an omega link, to a webbing with a web sling connector or to a wire rope with a thimble. The flat on the eye enables the assembly with an omega link or on a thimble. The Green Pin® Stainless Steel Sling Hook E is available in a range to suit 6 mm up to 13 mm grade 5 chain.

Certification on request: 2.1, 2.2, 3.1

**Material:** AISI 316L

**Temperature range:** -40°C up to +200°C

**Finish:** Polished

**Safety factor:** 4:1

**Grade:** 5

Part code	Chain diameter in	WLL (metric) tonnes	a in	b mm in	c in	dmm in	e mm in	f mm in	g mm in	h mm in	i mm in	j mm in	Weight lb
400300070110	7/32	0.7	3.39	0.93	1.02	0.59	0.75	1.69	2.83	4.49	0.37	0.24	0.62
400300120110	1/4-5/16	1.2	4.06	1.02	1.18	0.77	0.94	2.01	3.43	5.47	0.47	0.31	1.26
400300160110	3/8	1.6	5.08	1.42	1.3	0.94	1.1	2.56	4.17	6.73	0.57	0.39	2.25
400300270110	1/2	2.7	5.98	1.61	1.46	1.22	1.54	3.03	5.24	8.23	0.71	0.47	4.34

# Blueprint

