

## Snatch Block Green Pin® type 601S P-6951

---

### Product information



The Green Pin® Snatch Block S is a light-weight snatch block type 601S with a Green Pin® Shackle attached. The Green Pin® Snatch Block S has a smooth, uninterrupted pull due to conical roller bearings. Its coating ensures long-term durability, even under harsh conditions. The Green Pin® Snatch Block S is available in a range with a working load limit from 2 up to 125 ton in several sheave diameters for steel wire rope diam 7 up to 76 mm.

Certification on request: 2.1, 2.2, MTCb

... [Read more](#)

---

**Material:** Carbon steel, fitted with conical roller bearings

**Marking:** According to standard, CE-marked

**Finish:** Painted


**Standard:** EN 13157

**Note:** WLL is on the headfitting

**Safety factor:** 4:1

# Snatch Block Green Pin® type 601S P-6951

## Blueprint



## Technical data

Part code	Rope Ø range mm	WLL (metric) tonnes	Sheave dia mm	a in	b mm in	c in	dmm in	e mm in	Weight lb
4241BKOFFSS0302	7-9	2	75	2.95	11.46	1.69	3.23	3.43	8.53
4241BKOFFSS0404	10-12	4	115	4.53	14.29	2.28	4.72	3.5	14.02
4241BKOFFSS0804	10-12	4	200	7.87	18.82	2.28	8.27	4.69	25.79
4241BKOFFSS0604	12-14	4	150	5.91	16.42	2.28	6.3	3.5	19.05
4241BKOFFSS060816	14-16	8	150	5.91	18.82	2.68	6.3	4.69	32.85
4241BKOFFSS100816	14-16	8	250	9.84	22.87	2.68	10.24	4.09	57.32
4241BKOFFSS0608	20-22	8	150	5.91	18.82	2.68	6.3	4.69	31.09
4241BKOFFSS0808	20-22	8	200	7.87	20.75	2.68	8.27	4.69	42.77
4241BKOFFSS1008	20-22	8	250	9.84	22.87	2.68	10.24	4.09	54.45
4241BKOFFSS1208	20-22	8	300	11.81	25.43	2.68	12.2	4.17	70.55
4241BKOFFSS1608	20-22	8	400	15.75	29.76	2.68	16.34	4.69	77.16
4241BKOFFSS1408	20-22	8	350	13.78	27.2	2.68	14.17	4.69	88.18
4241BKOFFSS1808	20-22	8	450	17.72	32.17	2.68	18.31	4.69	126.77
4241BKOFFSS061216	14-16	12	150	5.91	21.69	3.27	6.3	4.69	44.97
4241BKOFFSS081216	14-16	12	200	7.87	22.83	3.27	8.27	4.92	62.83
4241BKOFFSS0612	20-22	12	150	5.91	21.69	3.27	6.3	4.69	44.09
4241BKOFFSS0812	20-22	12	200	7.87	22.83	3.27	8.27	4.92	62.17
4241BKOFFSS1012	20-22	12	250	9.84	26.73	3.27	10.24	4.92	76.06
4241BKOFFSS1212	20-22	12	300	11.81	29.45	3.27	12.2	5.75	109.13
4241BKOFFSS1412	20-22	12	350	13.78	30.43	3.27	14.17	5.71	127.87
4241BKOFFSS1612	20-22	12	400	15.75	32.36	3.27	16.14	6.69	148.81
4241BKOFFSS1812	20-22	12	450	17.72	34.53	3.27	18.31	6.69	180.78

## Snatch Block Green Pin® type 601S P-6951

### Technical data

Part code	Rope Ø range mm	WLL (metric) tonnes	Sheave dia mm	a in	b mm in	c in	dmm in	e mm in	Weight lb
4241BKOFFSS0615	24-26	15	150	5.91	23.03	3.62	6.3	5.43	54.67
4241BKOFFSS0815	24-26	15	200	7.87	25.43	3.62	8.27	5.59	66.14
4241BKOFFSS1015	24-26	15	250	9.84	27.76	3.62	10.24	5.75	95.9
4241BKOFFSS1215	24-26	15	300	11.81	30.35	3.62	12.2	5.59	113.54
4241BKOFFSS1415	24-26	15	350	13.78	31.42	3.62	14.37	6.73	138.89
4241BKOFFSS1615	24-26	15	400	15.75	33.39	3.62	16.34	6.69	153.22
4241BKOFFSS1815	24-26	15	450	17.72	35.35	3.62	18.31	6.69	182.98
4241BKOFFSS1422	28-32	22	350	13.78	37.4	4.96	14.37	7.09	207.23
4241BKOFFSS1622	28-32	22	405	15.94	39.65	4.96	16.34	7.09	242.51
4241BKOFFSS1822	28-32	22	450	17.72	41.61	4.96	18.31	7.09	273.37
4241BKOFFSS1830	28-32	30	450	17.72	43.35	5.43	18.31	8.27	480.61
4241BKOFFSS1630	32-38	30	405	15.94	42.36	5.43	16.34	8.27	306.44
4241BKOFFSS2332	28-32	32	280	23.39	49.21	5.43	24.02	7.6	617.29
4241BKOFFSS1632	28-35	32	188	16.34	41.73	5.43	16.85	7.6	414.47
4241BKOFFSS1832	28-38	32	210	18.39	43.74	5.43	18.9	7.6	462.97
4241BKOFFSS2032	28-38	32	240	19.88	45.35	5.43	20.47	7.6	529.11
4241BKOFFSS2036	28-38	36	250	19.88	47.28	6.3	20.47	7.99	551.16
4241BKOFFSS2354	38-51	54	468	24.53	60.63	7.09	25.12	10.59	1,031.76
4241BKOFFSS2375	44-51	75	637	24.53	71.46	7.48	25.12	10.47	1,404.35
4241BKOFFSS3075	44-57	75	780	29.49	76.97	7.48	30.31	10.47	1,719.61
4241BKOFFSS32100	64-67	100	1,186	33.27	91.1	9.37	33.86	10.24	2,614.68
4241BKOFFSS35125	70-76	125	1,363	37.4	98.98	10.83	37.99	10.24	3,004.9