

## Turnbuckles EH Eye - Hook Green Pin® G-6314

---

### Product information



The Green Pin® EH Turnbuckle is a turnbuckle with eye-hook end-fittings. One of the unique features of Green Pin® Turnbuckles such as this one is that they can be used for both lifting and lashing. Galvanization of the Green Pin® EE Turnbuckle ensures its long-term durability. The turnbuckle is available in a range with a diameter thread 3/8" (take up of 6") up to 1" (take up of 24").

Certification on request: 2.1, 2.2, 3.1, MTCa

**Standard:** generally to ASTM F1145-92 formerly U.S. Federal Specification FF-T-791b

... [Read more](#)

---

**Material:** drop forged high tensile steel SAE 1035 or 1045

**Marking:** CE-marked


**Temperature range:** -20°C up to +200°C

**Finish:** hot dipped galvanized

**Safety factor:** 5:1

# Turnbuckles EH Eye - Hook Green Pin® G-6314

## Blueprint



## Technical data

Part code	WLL (metric tonnes)	Thread	Take up inch	b mm in	c in	d mm in	e mm in	f mm in	g mm in	h mm in	i mm in	j mm in	Weight lb
422100540330	0.54	3/8	6	11.22	16.61	0.51	0.63	0.59	0.39	0.51	1.14	1.93	1.04
422100680330	0.68	1/2	12	18.35	29.53	0.51	0.75	0.63	0.47	0.71	1.42	2.24	2.82
422100100330	1	1/2	6	12.4	17.52	0.63	0.87	0.63	0.47	0.71	1.42	2.28	1.81
422100100335	1	1/2	9	15.35	23.54	0.63	0.87	0.63	0.47	0.71	1.42	2.24	2.34
422100100336	1.02	5/8	6	14.49	19.33	0.63	0.91	0.83	0.55	0.83	1.77	3.11	2.89
422100100337	1.02	5/8	12	20.43	31.34	0.63	0.91	0.83	0.55	0.83	1.77	3.07	3.77
422100140330	1.36	3/4	9	18.86	26.57	0.79	1.06	0.94	0.67	1.02	2.13	3.5	9.9
422100160330	1.59	5/8	9	17.44	25.35	0.79	0.94	0.83	0.55	0.83	1.77	3.07	3.44
422100230330	2.27	1	6	19.21	23.43	1.02	1.38	1.22	0.94	1.42	2.95	4.65	8.53
422100230335	2.27	1	18	31.06	47.32	1.02	1.38	1.22	0.94	1.42	2.95	4.61	13.23
422100230336	2.27	1	24	36.97	59.29	1.02	1.38	1.22	0.94	1.42	2.95	4.57	16.58
422100240330	2.36	3/4	6	15.87	20.51	0.87	1.06	0.94	0.67	1.02	2.13	3.5	4.5
422100240335	2.36	3/4	12	21.81	32.56	0.87	1.06	0.94	0.67	1.02	2.13	3.46	5.07
422100240336	2.36	3/4	18	27.83	44.61	0.87	1.06	0.94	0.67	1.02	2.13	3.5	6.28
422100450330	4.54	1	12	25.04	35.31	1.02	1.38	1.22	0.94	1.42	2.95	4.61	11.22