


Verope Steel Wire Rope Veropower 8

Product information



Wire rope construction: veropower 8 is a rotary swaged 8-strand, non-rotation-resistant rope in parallel lay construction with compacted outerstrands and a rope core covered with a plastic layer. It provides the highest breaking strength of all non rotation-resistant wire ropes and offers superior resistance to drum crushing.

Features:

- All strands are compacted and rotary swaged.
- Extremely high breaking strength and is very resistant against abrasion.
- Suitable for multi layer spooling systems with guided loads.
- Fully lubricated

ISO 4309

Rope Category No: Up to 40mm **RCN.09**, 41-46mm **RCN.11**, > 46mm **RCN.13**.

Marking: According to standard


Standard: EN 12385-4

Warning: veropower 8 may not be used with a swivel.


RCN: 09

Tolerance Ø: +2% to +4%

Overhead cranes



Mobile port crane



Offshore crane



Loading crane



Crawler crane



Container crane



Piling crane



Tower crane



Ladle crane



STS crane



Part code	Rope diameter mm	Tensile strength N/mm ²	Finish	Rope lay	Min. breaking force kN	Steel area mm ²	Lubrication	Weight lb
103101204270279	12	1,960	Galvanized	sZ	147.4	84	SupplierStandard	1.59
103101203270279	12	1,960	Galvanized	zS	147.4	84	SupplierStandard	1.59
103101204070279	12	1,960	Bright	sZ	147.4	84	SupplierStandard	1.59
103101203070279	12	1,960	Bright	zS	147.4	84	SupplierStandard	1.59
103101204300279	12	2,160	Galvanized	sZ	158.8	84	SupplierStandard	1.59
103101203300279	12	2,160	Galvanized	zS	158.8	84	SupplierStandard	1.59
103101204100279	12	2,160	Bright	sZ	158.8	84	SupplierStandard	1.59
103101203100279	12	2,160	Bright	zS	158.8	84	SupplierStandard	1.59
103101304270279	13	1,960	Galvanized	sZ	173	99	SupplierStandard	1.85
103101303270279	13	1,960	Galvanized	zS	173	99	SupplierStandard	1.85
103101304070279	13	1,960	Bright	sZ	173	99	SupplierStandard	1.85
103101303070279	13	1,960	Bright	zS	173	99	SupplierStandard	1.85
103101304300279	13	2,160	Galvanized	sZ	186.4	99	SupplierStandard	1.85
103101303300279	13	2,160	Galvanized	zS	186.4	99	SupplierStandard	1.85
103101304100279	13	2,160	Bright	sZ	186.4	99	SupplierStandard	1.85
103101303100279	13	2,160	Bright	zS	186.4	99	SupplierStandard	1.85
103101404270279	14	1,960	Galvanized	sZ	200.6	115	SupplierStandard	2.16
103101403270279	14	1,960	Galvanized	zS	200.6	115	SupplierStandard	2.16

103101404070279	14	1,960	Bright	sZ	200.6	115	SupplierStandard	2.16
103101403070279	14	1,960	Bright	zS	200.6	115	SupplierStandard	2.16
103101404300279	14	2,160	Galvanized	sZ	216.2	115	SupplierStandard	2.16
103101403300279	14	2,160	Galvanized	zS	216.2	115	SupplierStandard	2.16
103101404100279	14	2,160	Bright	sZ	216.2	115	SupplierStandard	2.16
103101403100279	14	2,160	Bright	zS	216.2	115	SupplierStandard	2.16
103101504270279	15	1,960	Galvanized	sZ	230.3	132	SupplierStandard	2.47
103101503270279	15	1,960	Galvanized	zS	230.3	132	SupplierStandard	2.47
103101504070279	15	1,960	Bright	sZ	230.3	132	SupplierStandard	2.47
103101503070279	15	1,960	Bright	zS	230.3	132	SupplierStandard	2.47
103101504300279	15	2,160	Galvanized	sZ	248.2	132	SupplierStandard	2.47
103101503300279	15	2,160	Galvanized	zS	248.2	132	SupplierStandard	2.47
103101504100279	15	2,160	Bright	sZ	248.2	132	SupplierStandard	2.47
103101503100279	15	2,160	Bright	zS	248.2	132	SupplierStandard	2.47
103101604270279	16	1,960	Galvanized	sZ	262	150	SupplierStandard	2.82
103101603270279	16	1,960	Galvanized	zS	262	150	SupplierStandard	2.82
103101604070279	16	1,960	Bright	sZ	262	150	SupplierStandard	2.82
103101603070279	16	1,960	Bright	zS	262	150	SupplierStandard	2.82
103101604270270	16	1,960	Galvanized	sZ	262	150	Dry	2.82
103101604300279	16	2,160	Galvanized	sZ	282.3	150	SupplierStandard	2.82
103101603300279	16	2,160	Galvanized	zS	282.3	150	SupplierStandard	2.82
103101604100279	16	2,160	Bright	sZ	282.3	150	SupplierStandard	2.82
103101603100279	16	2,160	Bright	zS	282.3	150	SupplierStandard	2.82

103101704270279	17	1,960	Galvanized	sZ	296.8	170	SupplierStandard	3.17
103101703270279	17	1,960	Galvanized	zS	296.8	170	SupplierStandard	3.17
103101704070279	17	1,960	Bright	sZ	296.8	170	SupplierStandard	3.17
103101703070279	17	1,960	Bright	zS	296.8	170	SupplierStandard	3.17
103101704300279	17	2,160	Galvanized	sZ	318.7	170	SupplierStandard	3.17
103101703300279	17	2,160	Galvanized	zS	318.7	170	SupplierStandard	3.17
103101704100279	17	2,160	Bright	sZ	318.7	170	SupplierStandard	3.17
103101703100279	17	2,160	Bright	zS	318.7	170	SupplierStandard	3.17
103101804270279	18	1,960	Galvanized	sZ	331.6	190	SupplierStandard	3.55
103101803270279	18	1,960	Galvanized	zS	331.6	190	SupplierStandard	3.55
103101804070279	18	1,960	Bright	sZ	331.6	190	SupplierStandard	3.55
103101803070279	18	1,960	Bright	zS	331.6	190	SupplierStandard	3.55
103101804300279	18	2,160	Galvanized	sZ	357.3	190	SupplierStandard	3.55
103101803300279	18	2,160	Galvanized	zS	357.3	190	SupplierStandard	3.55
103101804100279	18	2,160	Bright	sZ	357.3	190	SupplierStandard	3.55
103101803100279	18	2,160	Bright	zS	357.3	190	SupplierStandard	3.55
103101904270279	19	1,960	Galvanized	sZ	369.5	212	SupplierStandard	3.97
103101903270279	19	1,960	Galvanized	zS	369.5	212	SupplierStandard	3.97
103101904070279	19	1,960	Bright	sZ	369.5	212	SupplierStandard	3.97
103101903070279	19	1,960	Bright	zS	369.5	212	SupplierStandard	3.97
103101904300279	19	2,160	Galvanized	sZ	398.1	212	SupplierStandard	3.97
103101903300279	19	2,160	Galvanized	zS	398.1	212	SupplierStandard	3.97
103101904100279	19	2,160	Bright	sZ	398.1	212	SupplierStandard	3.97

103101903100279	19	2,160	Bright	zS	398.1	212	SupplierStandard	3.97
103102004270279	20	1,960	Galvanized	sZ	409.4	235	SupplierStandard	4.39
103102003270279	20	1,960	Galvanized	zS	409.4	235	SupplierStandard	4.39
103102004070279	20	1,960	Bright	sZ	409.4	235	SupplierStandard	4.39
103102003070279	20	1,960	Bright	zS	409.4	235	SupplierStandard	4.39
103102004300279	20	2,160	Galvanized	sZ	441.2	235	SupplierStandard	4.39
103102003300279	20	2,160	Galvanized	zS	441.2	235	SupplierStandard	4.39
103102004100279	20	2,160	Bright	sZ	441.2	235	SupplierStandard	4.39
103102003100279	20	2,160	Bright	zS	441.2	235	SupplierStandard	4.39
103102104270279	21	1,960	Galvanized	sZ	451.3	259	SupplierStandard	4.85
103102103270279	21	1,960	Galvanized	zS	451.3	259	SupplierStandard	4.85
103102104070279	21	1,960	Bright	sZ	451.3	259	SupplierStandard	4.85
103102103070279	21	1,960	Bright	zS	451.3	259	SupplierStandard	4.85
103102104300279	21	2,160	Galvanized	sZ	486.4	259	SupplierStandard	4.85
103102103300279	21	2,160	Galvanized	zS	486.4	259	SupplierStandard	4.85
103102104100279	21	2,160	Bright	sZ	486.4	259	SupplierStandard	4.85
103102103100279	21	2,160	Bright	zS	486.4	259	SupplierStandard	4.85
103102204270279	22	1,960	Galvanized	sZ	495.3	284	SupplierStandard	5.31
103102203270279	22	1,960	Galvanized	zS	495.3	284	SupplierStandard	5.31
103102204070279	22	1,960	Bright	sZ	495.3	284	SupplierStandard	5.31
103102203070279	22	1,960	Bright	zS	495.3	284	SupplierStandard	5.31
103102204300279	22	2,160	Galvanized	sZ	533.8	284	SupplierStandard	5.31
103102203300279	22	2,160	Galvanized	zS	533.8	284	SupplierStandard	5.31

103102204100279	22	2,160	Bright	sZ	533.8	284	SupplierStandard	5.31
103102203100279	22	2,160	Bright	zS	533.8	284	SupplierStandard	5.31
103102304270279	23	1,960	Galvanized	sZ	541.4	310	SupplierStandard	5.82
103102303270279	23	1,960	Galvanized	zS	541.4	310	SupplierStandard	5.82
103102304070279	23	1,960	Bright	sZ	541.4	310	SupplierStandard	5.82
103102303070279	23	1,960	Bright	zS	541.4	310	SupplierStandard	5.82
103102304300279	23	2,160	Galvanized	sZ	583.4	310	SupplierStandard	5.82
103102303300279	23	2,160	Galvanized	zS	583.4	310	SupplierStandard	5.82
103102304100279	23	2,160	Bright	sZ	583.4	310	SupplierStandard	5.82
103102303100279	23	2,160	Bright	zS	583.4	310	SupplierStandard	5.82
103102404270279	24	1,960	Galvanized	sZ	589.5	338	SupplierStandard	6.33
103102403270279	24	1,960	Galvanized	zS	589.5	338	SupplierStandard	6.33
103102404070279	24	1,960	Bright	sZ	589.5	338	SupplierStandard	6.33
103102403070279	24	1,960	Bright	zS	589.5	338	SupplierStandard	6.33
103102404300279	24	2,160	Galvanized	sZ	635.3	338	SupplierStandard	6.33
103102403300279	24	2,160	Galvanized	zS	635.3	338	SupplierStandard	6.33
103102404100279	24	2,160	Bright	sZ	635.3	338	SupplierStandard	6.33
103102403100279	24	2,160	Bright	zS	635.3	338	SupplierStandard	6.33
103102504270279	25	1,960	Galvanized	sZ	639.6	367	SupplierStandard	6.86
103102503270279	25	1,960	Galvanized	zS	639.6	367	SupplierStandard	6.86
103102504070279	25	1,960	Bright	sZ	639.6	367	SupplierStandard	6.86
103102503070279	25	1,960	Bright	zS	639.6	367	SupplierStandard	6.86
103102504300279	25	2,160	Galvanized	sZ	689.3	367	SupplierStandard	6.86

103102503300279	25	2,160	Galvanized	zS	689.3	367	SupplierStandard	6.86
103102504100279	25	2,160	Bright	sZ	689.3	367	SupplierStandard	6.86
103102503100279	25	2,160	Bright	zS	689.3	367	SupplierStandard	6.86
103102604270279	26	1,960	Galvanized	sZ	691.8	397	SupplierStandard	7.43
103102603270279	26	1,960	Galvanized	zS	691.8	397	SupplierStandard	7.43
103102604070279	26	1,960	Bright	sZ	691.8	397	SupplierStandard	7.43
103102603070279	26	1,960	Bright	zS	691.8	397	SupplierStandard	7.43
103102604300279	26	2,160	Galvanized	sZ	745.6	397	SupplierStandard	7.43
103102603300279	26	2,160	Galvanized	zS	745.6	397	SupplierStandard	7.43
103102604100279	26	2,160	Bright	sZ	745.6	397	SupplierStandard	7.43
103102603100279	26	2,160	Bright	zS	745.6	397	SupplierStandard	7.43
103102704270279	27	1,960	Galvanized	sZ	746.1	428	SupplierStandard	8
103102703270279	27	1,960	Galvanized	zS	746.1	428	SupplierStandard	8
103102704070279	27	1,960	Bright	sZ	746.1	428	SupplierStandard	8
103102703070279	27	1,960	Bright	zS	746.1	428	SupplierStandard	8
103102704300279	27	2,160	Galvanized	sZ	804	428	SupplierStandard	8
103102703300279	27	2,160	Galvanized	zS	804	428	SupplierStandard	8
103102704100279	27	2,160	Bright	sZ	804	428	SupplierStandard	8
103102703100279	27	2,160	Bright	zS	804	428	SupplierStandard	8
103102804270279	28	1,960	Galvanized	sZ	802.4	460	SupplierStandard	8.62
103102803270279	28	1,960	Galvanized	zS	802.4	460	SupplierStandard	8.62
103102804070279	28	1,960	Bright	sZ	802.4	460	SupplierStandard	8.62
103102803070279	28	1,960	Bright	zS	802.4	460	SupplierStandard	8.62

103102804300279	28	2,160	Galvanized	sZ	864.7	460	SupplierStandard	8.62
103102803300279	28	2,160	Galvanized	zS	864.7	460	SupplierStandard	8.62
103102804100279	28	2,160	Bright	sZ	864.7	460	SupplierStandard	8.62
103102803100279	28	2,160	Bright	zS	864.7	460	SupplierStandard	8.62
103102904270279	29	1,960	Galvanized	sZ	860.7	493	SupplierStandard	9.24
103102903270279	29	1,960	Galvanized	zS	860.7	493	SupplierStandard	9.24
103102904070279	29	1,960	Bright	sZ	860.7	493	SupplierStandard	9.24
103102903070279	29	1,960	Bright	zS	860.7	493	SupplierStandard	9.24
103102904300279	29	2,160	Galvanized	sZ	927.5	493	SupplierStandard	9.24
103102903300279	29	2,160	Galvanized	zS	927.5	493	SupplierStandard	9.24
103102904100279	29	2,160	Bright	sZ	927.5	493	SupplierStandard	9.24
103102903100279	29	2,160	Bright	zS	927.5	493	SupplierStandard	9.24
103103004270279	30	1,960	Galvanized	sZ	921.1	528	SupplierStandard	9.88
103103003270279	30	1,960	Galvanized	zS	921.1	528	SupplierStandard	9.88
103103004070279	30	1,960	Bright	sZ	921.1	528	SupplierStandard	9.88
103103003070279	30	1,960	Bright	zS	921.1	528	SupplierStandard	9.88
103103004300279	30	2,160	Galvanized	sZ	992.6	528	SupplierStandard	9.88
103103003300279	30	2,160	Galvanized	zS	992.6	528	SupplierStandard	9.88
103103004100279	30	2,160	Bright	sZ	992.6	528	SupplierStandard	9.88
103103003100279	30	2,160	Bright	zS	992.6	528	SupplierStandard	9.88
103103104270279	31	1,960	Galvanized	sZ	983.5	564	SupplierStandard	10.56
103103103270279	31	1,960	Galvanized	zS	983.5	564	SupplierStandard	10.56
103103104070279	31	1,960	Bright	sZ	983.5	564	SupplierStandard	10.56

103103103070279	31	1,960	Bright	zS	983.5	564	SupplierStandard	10.56
103103104300279	31	2,160	Galvanized	sZ	1,066	564	SupplierStandard	10.56
103103103300279	31	2,160	Galvanized	zS	1,066	564	SupplierStandard	10.56
103103104100279	31	2,160	Bright	sZ	1,066	564	SupplierStandard	10.56
103103103100279	31	2,160	Bright	zS	1,066	564	SupplierStandard	10.56
103103204270279	32	1,960	Galvanized	sZ	1,048	601	SupplierStandard	11.24
103103203270279	32	1,960	Galvanized	zS	1,048	601	SupplierStandard	11.24
103103204070279	32	1,960	Bright	sZ	1,048	601	SupplierStandard	11.24
103103203070279	32	1,960	Bright	zS	1,048	601	SupplierStandard	11.24
103103204300279	32	2,160	Galvanized	sZ	1,129	601	SupplierStandard	11.24
103103203300279	32	2,160	Galvanized	zS	1,129	601	SupplierStandard	11.24
103103204100279	32	2,160	Bright	sZ	1,129	601	SupplierStandard	11.24
103103203100279	32	2,160	Bright	zS	1,129	601	SupplierStandard	11.24
103103304270279	33	1,960	Galvanized	sZ	1,115	639	SupplierStandard	11.95
103103303270279	33	1,960	Galvanized	zS	1,115	639	SupplierStandard	11.95
103103304070279	33	1,960	Bright	sZ	1,115	639	SupplierStandard	11.95
103103303070279	33	1,960	Bright	zS	1,115	639	SupplierStandard	11.95
103103304300279	33	2,160	Galvanized	sZ	1,201	639	SupplierStandard	11.95
103103303300279	33	2,160	Galvanized	zS	1,201	639	SupplierStandard	11.95
103103304100279	33	2,160	Bright	sZ	1,201	639	SupplierStandard	11.95
103103303100279	33	2,160	Bright	zS	1,201	639	SupplierStandard	11.95
103103404270279	34	1,960	Galvanized	sZ	1,183	678	SupplierStandard	12.7
103103403270279	34	1,960	Galvanized	zS	1,183	678	SupplierStandard	12.7

103103404070279	34	1,960	Bright	sZ	1,183	678	SupplierStandard	12.7
103103403070279	34	1,960	Bright	zS	1,183	678	SupplierStandard	12.7
103103404300279	34	2,160	Galvanized	sZ	1,275	678	SupplierStandard	12.7
103103403300279	34	2,160	Galvanized	zS	1,275	678	SupplierStandard	12.7
103103404100279	34	2,160	Bright	sZ	1,275	678	SupplierStandard	12.7
103103403100279	34	2,160	Bright	zS	1,275	678	SupplierStandard	12.7
103103504270279	35	1,960	Galvanized	sZ	1,254	719	SupplierStandard	13.45
103103503270279	35	1,960	Galvanized	zS	1,254	719	SupplierStandard	13.45
103103504070279	35	1,960	Bright	sZ	1,254	719	SupplierStandard	13.45
103103503070279	35	1,960	Bright	zS	1,254	719	SupplierStandard	13.45
103103504300279	35	2,160	Galvanized	sZ	1,351	719	SupplierStandard	13.45
103103503300279	35	2,160	Galvanized	zS	1,351	719	SupplierStandard	13.45
103103504100279	35	2,160	Bright	sZ	1,351	719	SupplierStandard	13.45
103103503100279	35	2,160	Bright	zS	1,351	719	SupplierStandard	13.45
103103604270279	36	1,960	Galvanized	sZ	1,326	760	SupplierStandard	14.24
103103603270279	36	1,960	Galvanized	zS	1,326	760	SupplierStandard	14.24
103103604070279	36	1,960	Bright	sZ	1,326	760	SupplierStandard	14.24
103103603070279	36	1,960	Bright	zS	1,326	760	SupplierStandard	14.24
103103604300279	36	2,160	Galvanized	sZ	1,429	760	SupplierStandard	14.24
103103603300279	36	2,160	Galvanized	zS	1,429	760	SupplierStandard	14.24
103103604100279	36	2,160	Bright	sZ	1,429	760	SupplierStandard	14.24
103103603100279	36	2,160	Bright	zS	1,429	760	SupplierStandard	14.24
103103804270279	38	1,960	Galvanized	sZ	1,478	847	SupplierStandard	15.85

103103803270279	38	1,960	Galvanized	zS	1,478	847	SupplierStandard	15.85
103103804070279	38	1,960	Bright	sZ	1,478	847	SupplierStandard	15.85
103103803070279	38	1,960	Bright	zS	1,478	847	SupplierStandard	15.85
103103804300279	38	2,160	Galvanized	sZ	1,593	847	SupplierStandard	15.85
103103803300279	38	2,160	Galvanized	zS	1,593	847	SupplierStandard	15.85
103103804100279	38	2,160	Bright	sZ	1,593	847	SupplierStandard	15.85
103103803100279	38	2,160	Bright	zS	1,593	847	SupplierStandard	15.85
103104004270279	40	1,960	Galvanized	sZ	1,637	939	SupplierStandard	17.57
103104003270279	40	1,960	Galvanized	zS	1,637	939	SupplierStandard	17.57
103104004070279	40	1,960	Bright	sZ	1,637	939	SupplierStandard	17.57
103104003070279	40	1,960	Bright	zS	1,637	939	SupplierStandard	17.57
103104004300279	40	2,160	Galvanized	sZ	1,765	939	SupplierStandard	17.57
103104003300279	40	2,160	Galvanized	zS	1,765	939	SupplierStandard	17.57
103104004100279	40	2,160	Bright	sZ	1,765	939	SupplierStandard	17.57
103104003100279	40	2,160	Bright	zS	1,765	939	SupplierStandard	17.57
103104204270279	42	1,960	Galvanized	sZ	1,805	1,035	SupplierStandard	19.38
103104203270279	42	1,960	Galvanized	zS	1,805	1,035	SupplierStandard	19.38
103104204070279	42	1,960	Bright	sZ	1,805	1,035	SupplierStandard	19.38
103104203070279	42	1,960	Bright	zS	1,805	1,035	SupplierStandard	19.38
103104204300279	42	2,160	Galvanized	sZ	1,946	1,035	SupplierStandard	19.38
103104203300279	42	2,160	Galvanized	zS	1,946	1,035	SupplierStandard	19.38
103104204100279	42	2,160	Bright	sZ	1,946	1,035	SupplierStandard	19.38
103104203100279	42	2,160	Bright	zS	1,946	1,035	SupplierStandard	19.38

103104404270279	44	1,960	Galvanized	sZ	1,981	1,136	SupplierStandard	21.25
103104403270279	44	1,960	Galvanized	zS	1,981	1,136	SupplierStandard	21.25
103104404070279	44	1,960	Bright	sZ	1,981	1,136	SupplierStandard	21.25
103104403070279	44	1,960	Bright	zS	1,981	1,136	SupplierStandard	21.25
103104404300279	44	2,160	Galvanized	sZ	2,135	1,136	SupplierStandard	21.25
103104403300279	44	2,160	Galvanized	zS	2,135	1,136	SupplierStandard	21.25
103104404100279	44	2,160	Bright	sZ	2,135	1,136	SupplierStandard	21.25
103104403100279	44	2,160	Bright	zS	2,135	1,136	SupplierStandard	21.25
103104504270279	45	1,960	Galvanized	sZ	2,072	1,188	SupplierStandard	22.24
103104503270279	45	1,960	Galvanized	zS	2,072	1,188	SupplierStandard	22.24
103104504070279	45	1,960	Bright	sZ	2,072	1,188	SupplierStandard	22.24
103104503070279	45	1,960	Bright	zS	2,072	1,188	SupplierStandard	22.24
103104504300279	45	2,160	Galvanized	sZ	2,233	1,188	SupplierStandard	22.24
103104503300279	45	2,160	Galvanized	zS	2,233	1,188	SupplierStandard	22.24
103104504100279	45	2,160	Bright	sZ	2,233	1,188	SupplierStandard	22.24
103104503100279	45	2,160	Bright	zS	2,233	1,188	SupplierStandard	22.24
103104604270279	46	1,960	Galvanized	sZ	2,166	1,241	SupplierStandard	23.24
103104603270279	46	1,960	Galvanized	zS	2,166	1,241	SupplierStandard	23.24
103104604070279	46	1,960	Bright	sZ	2,166	1,241	SupplierStandard	23.24
103104603070279	46	1,960	Bright	zS	2,166	1,241	SupplierStandard	23.24
103104604300279	46	2,160	Galvanized	sZ	2,334	1,241	SupplierStandard	23.24
103104603300279	46	2,160	Galvanized	zS	2,334	1,241	SupplierStandard	23.24
103104604100279	46	2,160	Bright	sZ	2,334	1,241	SupplierStandard	23.24

103104603100279	46	2,160	Bright	zS	2,334	1,241	SupplierStandard	23.24
103104804270279	48	1,960	Galvanized	sZ	2,358	1,352	SupplierStandard	25.31
103104803270279	48	1,960	Galvanized	zS	2,358	1,352	SupplierStandard	25.31
103104804070279	48	1,960	Bright	sZ	2,358	1,352	SupplierStandard	25.31
103104803070279	48	1,960	Bright	zS	2,358	1,352	SupplierStandard	25.31
103104804300279	48	2,160	Galvanized	sZ	2,541	135	SupplierStandard	25.31
103104803300279	48	2,160	Galvanized	zS	2,541	1,352	SupplierStandard	25.31
103104804100279	48	2,160	Bright	sZ	2,541	1,352	SupplierStandard	25.31
103104803100279	48	2,160	Bright	zS	2,541	1,352	SupplierStandard	25.31

Technical data