

Alloy Bolt Type Shackle Crosby G-2130A

Product information



Design: Bolt Type Anchor shackles with thin head bolt – nut with cotter pin. Meets the performance requirements of Federal Specification R-C-271G, Type IVA, Grade B, Class 3, except for those provisions required of the contractor.

... [Read more](#)

Material: Forged Alloy Steel – Quenched and Tempered, with bow and bolt.

Marking: According to standard, CE-marked, WLL.

Finish: Hot dip galvanized.


Standard: DNV 2.7-1 Approved, US. FED. SPEC. RR-C-271, ISO 2415

Safety factor: 8

Grade: 8

Alloy Bolt Type Shackle Crosby G-2130A

Blueprint



Technical data

Part code	WLL (metric) tonnes	Size inch	A in	B in	C in	D, in	E in	F in	H, in	L in	Mmm in	Nmm in	A Tolerance +/- in	C Tolerance +/- in	Weight lb
420100200240	2	1/2	0.81	0.63	1.88	0.5	1.31	1.19	3.29	2.3	2.8	0.5	0.06	0.13	0.79
420100330240	3.25	5/8	1.06	0.75	2.38	0.63	1.69	1.5	4.17	2.93	3.56	0.69	0.06	0.25	1.37
420100480240	4.75	3/4	1.25	0.88	2.81	0.75	2.01	1.81	4.96	3.5	4.13	0.81	0.06	0.25	2.71
420100650240	6.5	7/8	1.44	1	3.31	0.88	2.28	2.09	5.83	4.02	4.8	0.97	0.06	0.25	3.95
420100850240	8.5	1	1.69	1.1	3.76	1	2.7	2.38	6.57	4.69	5.39	1.06	0.06	0.25	5.03
420100950240	9.5	1-1/8	1.81	1.25	4.25	1.13	2.91	2.7	7.48	5.16	5.91	1.25	0.06	0.25	8.27
420101200240	12	1-1/4	2.03	1.38	4.69	1.25	3.25	2.99	8.27	5.75	6.69	1.38	0.06	0.25	11.71
420101350240	13.5	1-3/8	2.24	1.5	5.24	1.38	3.62	3.31	9.17	6.38	7.2	1.5	0.13	0.25	15.81
420101700240	17	1-1/2	2.38	1.63	5.75	1.5	3.88	3.62	10	6.89	7.72	1.62	0.13	0.25	19