Industrial Rigging & Supply | Lifting Solutions Group Axel Johnson International

Crosby Sling Saver S-237

Product information



- High Performance Sling Connector is designed to connect to slings of all materials.
- Allows easy connection to master links or eye hooks and is ideal for bridles.
- Increased radius of bow gives wider sling bearing surface resulting in an increased area for load distribution, allows better load distribution on internal fibers.
  - Increases synthetic sling efficiency as compared to master links, shackle bows and conventional eye hooks. This allows 100% of the sling's rated Working Load Limit to be achieved.
- All alloy construction
- Each connector has a Product Identification Code (PIC) for material traceability, along with a frame size and the name Crosby forged into it.
- Crosby Sling Saver hardware meets the requirements for minimum stock diameter or thickness, and effective contact width shown in the Recommended Standards Specification for Synthetic Polyester Round Slings by the Web Sling & Tie Down Association. WSTDA-RS1.

... *Read more*

Material: Alloy steel

Safety factor: 4:1
Grade: 10

© November 2026 - All Rights Reserved

Industrial Rigging & Supply | Lifting Solutions Group Axel Johnson International

Crosby Sling Saver S-237

Blueprint



Technical data

Part code	WLL lb	A in	B in	C in	E in	G in	H in	L in	N in	R in	S in	W in	Weight lb
402200280340	6,250	0.88	1.42	2	3.18	1	0.8	4.21	1.04	2.92	0.48	1.38	1.15
402200570340	12,500	1.42	1.52	2.75	4.13	1.25	0.98	5.67	1.71	3.94	0.75	1.75	2.95
402200850340	18,750	1.63	1.58	2.75	4.37	1.38	1.1	6.5	2.04	4.45	0.93	1.88	4.74
402201420340	31,250	2	2.33	3.75	5.98	1.75	1.41	7.95	2.27	5.51	1.06	2.25	8.6
402201700340	37,500	2	2.2	3.75	6.18	1.75	1.41	7.83	2.27	5.39	1.06	2.38	9.24
402202270340	50,000	2.25	2.91	4.76	7.24	2.25	1.78	9.45	2.44	6.46	1.22	3.09	15.65
402203400340	75,000	2.56	3.36	5.75	9.13	2.31	1.86	11.06	3.07	7.72	1.5	3.16	26.01

© November 2026 - All Rights Reserved