

## Shackle Crosby G-2160E Wide Body

### Product information



All 2160E shackles are individually proof tested and magnetic particle inspected.

Proof tested as follows:

- 7-75 metric tons and 200-300 metric tons: 2 x WLL.
- 125 metric tons: 1.6 x WLL.

All ratings are in metric tons, embossed on side of bow.

Can be used to connect HIGH STRENGTH Synthetic Web Slings, HIGH STRENGTH Synthetic Round Slings or Wire Rope Slings.

Increase in shackle bow radius provides minimum 58% gain in sling bearing surface and eliminates need for a thimble.

Increases usable sling strength minimum of 15% and greatly improves life of wire rope slings.

RFID Equipped.

[... Read more](#)

**Material:** Forged alloy steel - quenched and tempered.

**Marking:** According to standard, CE-marked


**Temperature range:** -40°C up to +204°C

**Finish:** Bows are furnished Dimetcoated, and pins are Dimetcoated, then painted red.

**Standard:** DNV-OS-E101, DNV-ST-0377, DNV-ST-0378

## Shackle Crosby G-2160E Wide Body

### Blueprint



### Technical data

Part code	WLL (metric) tonnes	Effective body Ø mm	A in	B +/- 6.35 mm in	C in	D +/- .5 mm in	E in	G, in	H, in	J in	K in	Mmm in	Nmm in	Pmm in	Rmm in	Weight lb
420107501030	75	160	15.04	4.13	2.39	2.75	5.35	3.75	11.54	5	3.64	4.02	1.8	12.64	18.66	110.01
420112501030	125	173	17.72	5.12	3.1	3.15	6.5	3.75	14.37	5.91	4.33	4.02	1.8	15.47	22.99	190.04
420120001030	200	241	19.33	5.91	3.39	4.13	8.43	5.24	18.9	8.62	5.43	4.02	1.8	20.28	30.43	407.86
420130001030	300	290	22.6	7.36	4.29	5.24	10.51	6.14	23.62	10.39	6.3	4.02	1.8	23.94	37.52	787.05