



Swivel Hook with Bearing Crosby L-3322B

Product information

Bearing design allows hook to rotate freely under load. This hook incorporates QUIC-CHECK® deformation and angle indicators.

Material: Forged, Quenched & Tempered.

Safety factor: 5:1

Part code	WLL (metric) tonnes	A in	B in	C in	D, in	F in	G, in	H, in	J in	K in	L in	Mmm in	Omm in	Rmm in	S in	AA*mm in	Weight lb
420500201130	2	3	1.5	1.75	3.59	1.5	1	1.16	1.06	0.88	7.64	0.88	1	5.98	0.63	2	2.49
420500301130	3	3.5	1.56	2	3.98	1.62	1.13	1.31	1.19	0.94	8.58	0.94	1.09	6.69	0.75	2	3.79
420500501130	5	3.98	1.56	2.25	4.8	2	1.44	1.63	1.5	1.31	10.31	1.13	1.36	7.99	0.88	2.5	6.99
420500701130	7	5	1.94	2.75	6.26	2.5	1.81	2.06	1.78	1.66	12.83	1.44	1.61	9.88	1.13	3	14
420501101130	11	5.59	2.05	3.12	7.52	3	2.25	2.63	2.41	1.88	15.24	1.63	2.08	11.73	1.25	3.98	22.27
420501501130	15	7.09	3.62	4.09	8.31	3.25	2.59	2.94	2.62	2.19	18.62	1.94	2.27	14.41	1.5	3.98	35.94

Blueprint

