



Swivel hook Crosby L-322 AN

Product information

Features:

- Suitable for positioning of the hook before the load is lifted.
- Swivel hooks are load rated.
- Proper design, careful forging, and precision controlled quench and tempering gives maximum strength without excessive weight and bulk.
- Hoist hooks incorporate markings forged into the product which address two (2) QUIC-CHECK®
- Deformation Indicators -- Two strategically placed marks, one just below the shank or eye and the other on the hook tip, which allows for a QUIC-CHECK® measurement to determine if the throat opening has changed, thus indicating abuse or overload.
- Angle Indicators — Indicates the maximum included angle which is allowed between two (2) sling legs in the hook. These indicators also provide the opportunity to approximate other included angles between two sling legs.

Material: Alloy steel - Forged, Quenched & Tempered.

Marking: CE-marked

Note: This hook is a positioning device and is not intended to rotate under load.

Safety factor: 4:1

Grade: 8

Part code	WLL (metric) tonnes	EWL mm	A in	B in	C in	D, in	F in	G, in	H, in	L in	O*mm in	Rmm in	S in	AA**mm in	Weight lb
420500130750	1.25	116	2.01	0.82	1.25	2.85	1.25	0.73	0.81	5.67	0.93	4.57	0.38	1.5	0.75
420500160750	1.6	136	2.5	1.31	1.5	3.15	1.38	0.84	0.94	6.69	0.97	5.35	0.5	2	1.26
420500250750	2.5	155	2.99	1.5	1.75	3.58	1.5	1	1.16	7.36	1.06	6.1	0.63	2	2.25
420500320750	3.2	165	2.99	1.5	1.75	4.02	1.62	1.13	1.31	8.27	1.16	6.5	0.63	2	2.29
420500540750	5.4	191	3.5	1.64	2	4.84	2.01	1.44	1.63	9.69	1.41	7.52	0.75	2.5	4.96
420500800750	8	245	4.57	2.28	2.5	6.3	2.5	1.81	2.07	12.48	1.69	9.65	1	3	10.3
420501150750	11.5	289	5	2.44	2.76	7.56	2.99	2.24	2.64	14.76	2.22	11.38	1.13	3.98	19.4
420501600750	16	311	5.63	2.48	3.11	8.35	3.25	2.6	2.93	16.42	2.4	12.24	1.25	3.98	23.15
420502200750	22	424	7.09	3.76	4.09	10.35	4.25	2.99	3.5	21.34	3.19	16.69	1.5	5	46.96
420503150750	31.5	459	7.09	3.76	4.09	13.62	5	3.66	4.65	23.23	3.25	18.07	1.5	6.5	70.55

Blueprint

