

## Master Link Hybrid MFH

---

### Product information



Designed for crane hooks DIN 15401 and 15402. Designed for use with CL, CLD, CG and CGD. 3- and 4-leg chain slings require CLD / CGD.

... [Read more](#)

---

**Material:** Quenched and tempered alloy steel grade 10.

**Marking:** According to standard, code and grade.

**Finish:** Painted.

**Standard:** EN 1677


**Warning:** Not to be heat treated.

**Safety factor:** 5:1

**Grade:** 10

## Master Link Hybrid MFH

### Blueprint



### Technical data

Part code	Code	WLL (metric) tonnes	For chain, 1-leg mm	For chain, 2-leg mm	For chain, 3-4-leg mm	For crane hooks	D, in	E in	L in	Weight lb
402100750120	MFH-1310-10	7.5	13	10	8	12	0.87	4.92	9.06	4.63
402101000120	MFH-1613-10	10	16	13	10	12	1.1	5.31	9.84	8.16
402101700120	MFH-2016-10	17	20	16	13	16	1.26	5.31	11.02	11.68
402102800120	MFH-2220-10	28	26	20	16	25	1.57	6.89	12.6	21.38
402102800121	MFHW-2220-10	28	26	20	16	50	1.57	8.86	13.98	24.47