



Snatch Block McKissick 401 - 402 Tail Board - All Alloy

Product information

General:

The McKissick snatch blocks 401 and 402 from Crosby are Tail board type snatch blocks. The entire block is made from heat treated alloy steel which results in a weight reduction up to 40% in compare to non-alloy steel blocks with the same WLL.

Model 402 Available in WLL 12 and can be delivered with bronze bushing (BB) and with roller bearing (RB).

Model 401 Available from 25 up to 60 T. Only available with bronze bushing (BB).

Features:

- Bolt for opening feature is retained, to ensure no lost bolts.
- Opening feature permits easy insertion of rope without reeving, or while the block is suspended.
- Center pin equipped with pressure lube fitting.
- All sizes feature sheave grooves suited for a range of wire line diameters.
- Meets or exceeds all requirements of ASME B30.26 including identification ductility, design factor, proof load and temperature requirements.
- Meet other critical performance requirements including fatigue life and material traceability, not addressed by ASME B30.26.

Material: Forged Alloy steel.

Safety factor: 4:1

Part code	Code	Rope Ø range mm	Rope Ø range inch	WLL (metric) tonnes	Sheave dia mm	Bearing	Ain	B mmin	C mmin	D mmin	E mmin	F mmin	G mmin	Weight
424101200350	402	19-22	3/4 - 7/8	12	152	BB mm	9.88	5.98	4.17	1.81	0.98	5.12	1.61	6.8
424101200355	402	19-22	3/4 - 7/8	12	152	RB	9.88	5.98	4.17	1.81	0.98	5.12	1.61	6.8
424101200356	402	19-22	3/4 - 7/8	12	203	BB mm	11.93	8.11	4.17	1.81	0.98	6.1	1.61	9.5
424101200357	402	19-22	-	12	203	RB	11.93	8.11	4.17	1.81	0.98	6.1	1.61	9.5
424112003511	402	19-22	3/4 - 7/8	12	44.5	BB mm	11.93	8.11	4.17	1.81	0.98	6.1	1.61	9.5
424101200358	402	19-22	-	12	254	BB mm	14.02	10.12	4.17	1.81	0.98	7.2	1.69	13.2
424101200359	402	19-22	3/4 - 7/8	12	254	RB	14.02	10.12	4.17	1.81	0.98	7.2	1.69	13.2
424112003510	402	19-22	3/4 - 7/8	12	44.5	BB mm	14.02	10.12	4.17	1.81	0.98	7.2	1.69	13.2
424102500350	401	26-32	1 - 1-1/4	25	203	BB mm	13.5	8.27	6.14	2.56	1.5	7.13	2.36	22.7
424102500355	401	26-32	1 - 1-1/4	25	203	BB mm	15.43	10.24	6.14	2.56	1.5	8.19	2.44	29.5
424103000350	401	26-32	1 - 1-1/4	30	305	BB mm	18.62	12.24	7.01	3.03	1.73	10	3.11	43.1
424103000355	401	26-32	1 - 1-1/4	30	356	BB mm	20.87	14.25	7.01	3.03	1.73	11.26	3.39	49.9
424106000350	401	26-32	1 - 1-1/4	60	305	BB mm	20.31	12.13	8.66	2.8	2.52	10.75	3.5	43.1

Blueprint

