



Snatch Block McKissick 416 - 434 with Hook - All Alloy

Product information

General:

The McKissick snatch blocks 416 and 434 from Crosby are snatch blocks fitted with a hook. The entire blocks are made from heat treated alloy steel which results in a weight reduction up to 40% in compare to non-alloy steel blocks with the same WLL.

Model 416 Available in WLL 12 and can be delivered with bronze bushing (BB) and with roller bearing (RB).

Model 434 Available from 25 up to 30 T. Only available with bronze bushing (BB).

Features:

- Bolt for opening feature is retained, to ensure no lost bolts.
- Opening feature permits easy insertion of rope without reeving, or while the block is suspended.
- Center pin equipped with pressure lube fitting.
- All sizes feature sheave grooves suited for a range of wire line diameters.
- Meets or exceeds all requirements of ASME B30.26 including identification ductility, design factor, proof load and temperature requirements.
- Meet other critical performance requirements including fatigue life and material traceability, not addressed by ASME B30.26.

Material: Heat treated alloy steel.

Marking: CE-marked

Part code	Code	Rope Ø range mm	Rope Ø range inch	WLL (metric) tonnes	Sheave dia mm	Bearing	Ain	B mmin	C mmin	D mmin	E mmin	F mmin	G mmin	H mmin	Weight lb
424101200390	416	19-22	3/4 - 7/8	12	152	BB mm	19.88	5.98	4.17	7.87	1.57	14.25	1.46	2.64	26.01
424101200395	416	19-22	3/4 - 7/8	12	152	RB	19.88	5.98	4.17	7.87	1.57	14.25	1.46	2.64	26.01
424101200396	416	19-22	3/4 - 7/8	12	203	BB mm	21.97	8.11	4.17	7.87	1.57	15.28	1.46	2.64	33.07
424101200397	416	19-22	3/4 - 7/8	12	203	RB	21.97	8.11	4.17	7.87	1.57	15.28	1.46	2.64	33.07
424101200398	416	19-22	3/4 - 7/8	12	254	BB mm	24.02	10.12	4.17	7.87	1.57	16.34	1.46	2.64	41.01
424101200399	416	19-22	3/4 - 7/8	12	254	RB	24.02	10.12	4.17	7.87	1.57	16.34	1.46	2.64	41.01
424102500390	434	26-32	1 - 1-1/4	25	203	BB mm	26.57	8.27	6.14	9.37	2.01	19.06	1.5	3.39	89.95
424102500395	434	26-32	1 - 1-1/4	25	254	BB mm	28.62	10.24	6.14	9.37	2.01	20.12	1.5	3.39	106.92
424103000390	434	26-32	1 - 1-1/4	30	305	BB mm	36.34	12.24	7.01	11.77	2.52	25.87	1.93	4.33	164.91
424103000395	434	26-32	1 - 1-1/4	30	356	BB mm	38.58	14.25	7.01	11.77	2.52	27.13	1.93	4.33	179.9

Blueprint

