



Snatch Block McKissick 430 with Hook - Super Champion

Product information

The McKissick snatch block 430 Super Champion from Crosby is a snatch block fitted with a hook. Available from 20 up to 30 T. Can be delivered with bronze bushing (BB) and with roller bearing (RB).

Features:

- Bolt for opening feature is retained, to ensure no lost bolts.
- Opening feature permits easy insertion of rope without reeving, or while the block is suspended.
- Center pin equipped with pressure lube fitting.
- All sizes feature sheave grooves suited for a range of wire line diameters.
- Meets or exceeds all requirements of ASME B30.26 including identification ductility, design factor, proof load and temperature requirements.
- Meet other critical performance requirements including fatigue life and material traceability, not addressed by ASME B30.26.

Material: Forged steel.

Marking: CE-marked

Safety factor: 4:1

Part code	Code	Rope Ø range mm	Rope Ø range inch	WLL (metric) tonnes	Sheave dia mm	Bearing	Ain	B mmin	C mmin	D mmin	E mmin	F mmin	G mmin	H mmin	Weight lb
424102000300	430	26-29	1 - 1-1/8	20	203	BB	25.87	8.11	5.98	9.41	2.01	18.43	1.5	3.39	74.96
424102000305	430	26-29	1 - 1-1/8	20	203	RB	25.87	8.11	5.98	9.41	2.01	18.43	1.5	3.39	74.96
424102000306	430	26-29	1 - 1-1/8	20	254	BB	27.95	10.12	5.98	9.41	2.01	19.49	1.5	3.39	89.07
424102000307	430	26-29	1 - 1-1/8	20	254	RB	27.95	10.12	5.98	9.41	2.01	19.49	1.5	3.39	89.07
424102000308	430	26-29	1 - 1-1/8	20	305	BB	30	12.24	5.98	9.41	2.01	20.51	1.5	3.39	102.96
424102000309	430	26-29	1 - 1-1/8	20	305	RB	30	12.24	5.98	9.41	2.01	20.51	1.5	3.39	102.96
4241020003010	430	26-29	1 - 1-1/8	20	356	BB	32.32	14.02	5.98	9.41	2.01	21.97	1.5	3.39	123.02
4241020003011	430	26-29	1 - 1-1/8	20	356	RB	32.32	14.02	5.98	9.41	2.01	21.97	1.5	3.39	123.02
424102500300	430	26-32	1 - 1-1/4	25	457	BB	41.42	18.27	7.13	11.77	2.52	27.95	1.93	4.33	240.08
424102500305	430	26-32	1 - 1-1/4	25	457	RB	41.42	18.27	7.13	11.77	2.52	27.95	1.93	4.33	240.08
424103000300	430	26-32	1 - 1-1/4	30	508	BB	52.17	20.24	8.31	15.24	2.99	36.1	2.24	5.91	375.01
424103000305	430	26-32	1 - 1-1/4	30	508	RB	52.17	20.24	8.31	15.24	2.99	36.1	2.24	5.91	375.01
424103000306	430	26-32	1 - 1-1/4	30	610	BB	55.75	24.25	8.31	15.24	2.99	37.76	2.24	5.91	449.96
424103000307	430	26-32	1 - 1-1/4	30	610	RB	55.75	24.25	8.31	15.24	2.99	37.76	2.24	5.91	449.96

Blueprint

