



Snatch Block McKissick 431 with Shackle - Super Champion

Product information

The McKissick snatch block 431 Super Champion from Crosby is a snatch block fitted with a shackle. Available from 20 up to 30 T. Can be delivered with bronze bushing (BB) and with roller bearing (RB).

Features:

- Bolt for opening feature is retained, to ensure no lost bolts.
- Opening feature permits easy insertion of rope without reeving, or while the block is suspended.
- Center pin equipped with pressure lube fitting.
- All sizes feature sheave grooves suited for a range of wire line diameters.
- Meets or exceeds all requirements of ASME B30.26 including identification ductility, design factor, proof load and temperature requirements.
- Meet other critical performance requirements including fatigue life and material traceability, not addressed by ASME B30.26.

Material: Forged steel.

Marking: CE-marked

Safety factor: 4:1

Part code	Code	Rope Ø range mm	Rope Ø range inch	WLL (metric) tonnes	Sheave dia mm	Bearing	Ain	B mmin	C mmin	D mmin	E mmin	F mmin	G mmin	H mmin	Weight lb
424102000420	431	26-29	1 - 1-1/8	20	203	BB mm	26.57	8.11	5.98	19.76	2.01	2.76	3.7	3.98	91.93
424102000425	431	26-29	1 - 1-1/8	20	203	RB	26.57	8.11	5.98	19.76	2.01	2.76	3.7	3.98	91.93
424102000426	431	26-29	1 - 1-1/8	20	254	BB mm	28.62	10.12	5.98	20.71	2.01	2.76	3.7	4.02	111.99
424102000427	431	26-29	1 - 1-1/8	20	254	RB	28.62	10.12	5.98	20.71	2.01	2.76	3.7	4.02	111.99
424102000428	431	26-29	1 - 1-1/8	20	305	BB mm	30.67	12.24	5.98	21.77	2.01	2.76	3.7	4.02	130.07
424102000429	431	26-29	1 - 1-1/8	20	305	RB	30.67	12.24	5.98	21.77	2.01	2.76	3.7	4.02	130.07
4241020004210	431	26-29	1 - 1-1/8	20	356	BB mm	32.99	14.02	5.98	23.27	2.01	2.76	3.7	4.02	160.06
4241020004211	431	26-29	1 - 1-1/8	20	356	RB	32.99	14.02	5.98	23.27	2.01	2.76	3.7	4.02	160.06
424102500420	431	26-32	1 - 1-1/4	25	457	BB mm	41.38	18.27	7.13	29.13	2.01	3.11	3.5	4.8	270.07
424102500425	431	26-32	1 - 1-1/4	25	457	RB	41.38	18.27	7.13	29.13	2.01	3.11	3.5	4.8	279.99
424103000425	431	26-32	1 - 1-1/4	30	508	RB	52.4	20.24	8.31	34.41	2.52	3.94	5.63	7.05	485.02
424103000420	431	26-32	1 - 1-1/4	30	508	BB mm	52.4	20.24	8.31	38.35	2.52	3.94	5.63	7.05	503.1
424103000427	431	26-32	1 - 1-1/4	30	610	RB	55.98	24.25	8.31	40	2.52	3.94	5.63	7.05	574.97
424103000426	431	26-32	1 - 1-1/4	30	610	BB mm	55.98	24.25	8.31	40	2.52	3.94	5.63	7.05	580.92

Blueprint

