



## Snatch Block McKissick 418 with Hook - Light Champion

### Product information

The McKissick snatch block 418 Light Champion from Crosby is a snatch block fitted with a hook. Available from WLL 2 up to 15 T. Can be delivered with bronze bushing (BB) and from WLL 8 T also with roller bearing (RB).

#### Features:

- Bolt for opening feature is retained, to ensure no lost bolts.
- Opening feature permits easy insertion of rope without reeving, or while the block is suspended.
- Center pin equipped with pressure lube fitting.
- All sizes feature sheave grooves suited for a range of wire line diameters.
- Meets or exceeds all requirements of ASME B30.26 including identification ductility, design factor, proof load and temperature requirements.
- Meet other critical performance requirements including fatigue life and material traceability, not addressed by ASME B30.26.

**Material:** Forged steel.

**Marking:** CE-marked

**Safety factor:** 4:1

Part code	Code	Rope Ø range mm	Rope Ø range inch	WLL (metric) tonnes	Sheave dia mm	Bearing	Ain	B mmin	C mmin	D mmin	E mmin	F mmin	G mmin	H mmin	Weight lb
424100200230	418	8-10	5/16 - 3/8	2	76	BB	9.72	1.85	2.64	3.58	0.75	6.46	0.75	0.98	5.07
424100400230	418	10-13	3/8 - 1/2	4	114	BB	14.13	4.25	3.11	5.24	0.98	10.12	0.94	1.85	11.9
424100800230	418	16-19	5/8 - 3/4	8	152	BB	18.94	5.98	4.17	6.81	1.57	13.54	1.3	2.4	26.9
424100800235	418	16-19	5/8 - 3/4	8	152	RB	18.94	5.98	4.17	6.81	1.57	13.54	1.3	2.4	26.9
424100800236	418	16-19	5/8 - 3/4	8	203	BB	21.02	8.11	4.17	6.81	1.57	14.53	1.3	2.4	33.07
424100800237	418	16-19	5/8 - 3/4	8	203	RB	21.02	8.11	4.17	6.81	1.57	14.53	1.3	2.4	33.07
424100800238	418	16-19	5/8 - 3/4	8	254	BB	23.07	10.12	4.17	6.81	1.57	15.59	1.3	2.4	41.01
424100800239	418	16-19	5/8 - 3/4	8	254	RB	23.07	10.12	4.17	6.81	1.57	15.59	1.3	2.4	41.01
4241008002310	418	16-19	5/8 - 3/4	8	305	BB	25.91	12.13	4.17	6.81	1.57	17.4	1.3	2.4	48.06
4241008002311	418	16-19	5/8 - 3/4	8	305	RB	25.91	12.13	4.17	6.81	1.57	17.4	1.3	2.4	48.06
4241008002312	418	16-19	5/8 - 3/4	8	356	BB	27.4	14.13	4.17	6.81	1.57	17.91	1.3	2.4	54.9
4241008002313	418	16-19	5/8 - 3/4	8	356	RB	27.4	14.13	4.17	6.81	1.57	17.91	1.3	2.4	54.9
424101500230	418	19-22	3/4 - 7/8	15	406	BB	32.24	16.1	5.08	8.35	1.77	21.26	1.46	2.91	130.07
424101500235	418	19-22	3/4 - 7/8	15	406	RB	33.5	18.11	5.08	8.35	1.77	21.5	1.5	2.91	130.07
424101500236	418	22-26	7/8 - 1	15	457	BB	33.5	18.11	5.08	8.35	1.77	21.5	1.5	2.91	149.91
424101500237	418	22-26	7/8 - 1	15	457	RB	33.5	18.11	5.08	8.35	1.77	21.5	1.5	2.91	149.91

# Blueprint

