

Loadlink Plus

Product information



Loadlink plus is designed to be rigged with Crosby standard shackles - digital dynamometer tension load cell known worldwide as the original electronic force measurement device to feature an integral display, the Loadlink plus has been in production since 1979. Over the years the line has been expanded and the Loadlink plus is now used on a daily basis for load monitoring and heavy lifts ranging in capacity from 1t to 300t, by a variety of industrial and commercial industries including manufacturing, transportation, agriculture, oil and gas, utilities, aerospace and clean energy.

Features

- Large 25mm/1" LCD display
- High Accuracy of +/-0.1% full scale
- Selectable Units - t, lbs, kg or kN
- High Resolution, 5000 divisions as standard
- Peak Hold – 100Hz peak force analysis
- Push button tare
- Preset tare
- Compact Size
- Lightweight
- 90db Audible set point alarm
- Design validated by F.E.A.
- Battery life of 80 hours continuous
- Display type - 6 digit 25mm LCD

Supplied with the following as standard

- Proof test certificate

[... Read more](#)


Material: Aluminium 2014-T6, load bearing bushes EN24T

Temperature range: -10°C up to +50°C

Finish: Black anodized to BS EN 12373-1:2001 Class 10. Bushes clear passivated.

Loadlink Plus

Blueprint



Technical data

Part code	Code	WLL (metric) tonnes	Safety factor	Resolution kg	Loading pin Ø mm	A in	B in	C in	D, in	Ø E mm in	F in	G, in	Weight lb
423500100270	LLP1T	1	12:1	0.5	19	8.03	1.69	4.09	5.75	0.96	1.89	0.75	3.31
423500250270	LLP2T5	2.5	7:1	1	19	8.03	1.69	4.09	5.75	0.96	1.89	0.75	3.31
423500650270	LLP6T5	6.5	7:1	1	25	9.8	1.69	4.45	6.5	1.5	2.56	1.26	5.29
423501200270	LLP12T	12	7:1	2	35	12.01	1.85	4.45	7.6	1.87	-	-	8.16
423502500270	LLP25T	25	5:1	5	51	13.39	2.36	4.53	8.46	2.17	-	-	11.02
423503500270	LLP35T	35	5:1	5	57	15.47	2.95	4.96	8.86	2.36	-	-	18.96
423505500270	LLP55T	55	5:1	10	57	16.69	2.95	7.09	9.06	2.99	-	-	28.66
423507500270	LLP75T	75	5:1	10	70	18.5	2.95	7.95	10.24	2.99	-	-	35.27
423510000270	LLP100T	100	5:1	50	83	23.94	3.9	10.04	12.6	4.29	-	-	74.96
423515000270	LLP150T	150	4:1	50	95	26.38	3.9	11.93	14.17	4.29	-	-	101.41
423520000270	LLP200T	200	5:1	100	121	27.56	5.67	13.78	13.78	5.71	-	-	180.78
423525000270	LLP250T	250	4:1	100	127	27.56	5.67	13.78	13.78	5.71	-	-	180.78
423530000270	LLP300T	300	5:1	100	152	31.73	5.91	16.77	13.78	6.3	-	-	260.15