



## Swivel Jaw & Jaw Crosby AS-2

### Product information

Swivels with jaw-jaw, designed for high rotation speed.

- Lower torque required to initiate rotation.
- Angular contact bearings maximize efficiency, reliability, and service life of swivel and extend the life of the wire rope.
- Entire swivel is zinc plated to resist corrosion.
- Individually Proof Tested to 2 times the Working Load Limit with certification.
- Hook models utilize genuine Crosby hooks which are forged alloy steel, quenched and tempered, and contain patented QUIC-CHECK® markings.
- Each swivel 7.65 metric tons and larger is furnished with a pressure lubrication fitting.

**Marking:** CE-marked

**Safety factor:** 5:1

Part code	WLL (metric tonnes)	A in	B mmin	C mmin	D mmin	E mmin	F mmin	G mmin	H mmin	Weight lb
422500040400	0.4	0.88	2.38	3.13	0.38	0.25	0.25	0.19	0.41	0.4
422500070400	0.68	1.31	3.54	4.45	0.44	0.31	0.38	0.22	0.56	0.9
422500140400	1.35	1.63	4.06	5.43	0.69	0.5	0.5	0.28	0.78	2.01
422500270400	2.7	2.01	6.26	8.15	0.94	0.75	0.75	0.38	1.19	4.89
422500450400	4.5	2.5	7.76	10.63	1.13	1	0.88	0.53	1.53	9.59
422500770400	7.65	2.99	9.65	12.32	1.34	1.56	1.19	0.56	2.09	15.81
422500900400	9	4.02	14.02	17.52	1.75	1.75	1.5	0.81	3.5	39.9
422501350400	13.5	4.02	14.02	17.52	1.75	1.75	1.5	0.81	3.5	39.9
422502250400	22.5	5	15.94	20.71	2.38	2.01	2.01	1.13	3.68	78.04
422503150400	31.5	5	15.94	20.71	2.38	2.01	2.01	1.13	3.68	78.04

# Blueprint

