



Swivel Jaw & Hook Crosby AS-1

Product information

Swivel with jaw-hook, designed for high rotation speed.

- Lower torque required to initiate rotation.
- Angular contact bearings maximize efficiency, reliability, and service life of swivel and extend the life of the wire rope.
- Entire swivel is zinc plated to resist corrosion.
- Individually Proof Tested to 2 times the Working Load Limit with certification.
- Hook models utilize genuine Crosby hooks which are forged alloy steel, quenched and tempered, and contain patented QUIC-CHECK® markings.
- Each swivel 7.65 metric tons and larger is furnished with a pressure lubrication fitting.

Marking: CE-marked

Safety factor: 5:1

Part code	Rope Ø range mm	WLL (metric) tonnes	Ain	B mmin	C mmin	D mmin	E mmin	F mmin	G mmin	H mmin	I mmin	Weight lb
422500040390	3	0.4	0.88	0.25	0.25	0.38	0.41	4.33	2.85	0.93	0.73	0.71
422500070390	6	0.68	1.31	0.38	0.31	0.44	0.56	5.43	3.15	0.97	0.84	1.5
422500140390	10	1.35	1.63	0.5	0.5	0.69	0.78	6.34	4.02	1.16	1.14	2.29
422500270390	13	2.7	2.01	0.75	0.75	0.94	1.19	8.7	4.84	1.41	1.44	6.5
422500450390	16	4.5	2.5	0.88	1	1.13	1.53	10.71	6.3	1.69	1.82	12.9
422500770390	19	7.65	2.99	1.19	1.56	1.34	2.09	13.66	8.35	2.4	2.6	26.46
422500900390	22	9	4.02	1.5	1.75	1.75	3.5	17.95	10.35	3.19	2.99	52.91
422501350390	25	13.5	4.02	1.5	1.75	1.75	3.5	17.95	10.35	3.19	2.99	52.91
422502250390	32	22.5	5	2.01	2.01	2.38	3.68	20.87	13.62	3.25	3.62	97
422503150390	38	31.5	5	2.01	2.01	2.38	3.68	24.02	14.06	2.99	4.57	139.99

Blueprint

