



Swivel Eye & Eye Crosby AS-5

Product information

Swivels with eye-eye, designed for high rotation speed.

- Lower torque required to initiate rotation.
- Angular contact bearings maximize efficiency, reliability, and service life of swivel and extend the life of the wire rope.
- Entire swivel is zinc plated to resist corrosion.
- Individually Proof Tested to 2 times the Working Load Limit with certification.
- Hook models utilize genuine Crosby hooks which are forged alloy steel, quenched and tempered, and contain patented QUIC-CHECK® markings.
- Each swivel 7.65 metric tons and larger is furnished with a pressure lubrication fitting.

Marking: CE-marked

Safety factor: 5:1

Part code	Rope Ø range mm	WLL (metric) tonnes	Ain	B mmin	C mmin	D mmin	E mmin	F mmin	G mmin	Weight lb
422500040350	3	0.4	0.88	2.64	3.39	0.38	0.25	0.25	0.81	0.31
422500070350	6	0.68	1.31	3.74	4.65	0.44	0.31	0.38	0.88	0.9
422500140350	10	1.35	1.63	4.33	5.55	0.63	0.5	0.66	1.34	1.81
422500270350	13	2.7	2.01	6.14	8.15	1	0.75	0.91	2.01	4.3
422500450350	16	4.5	2.5	7.76	10.63	1.19	1	1.25	2.64	8.6
422500770350	19	7.65	2.99	9.33	12.32	1.5	1.25	1.41	3.13	15.43
422500900350	22	9	4.02	13.9	17.52	1.81	1.72	1.63	4.69	37.04
422501350350	25	13.5	4.02	13.27	17.52	2.13	2.01	2.13	4.69	39.02
422502250350	32	22.5	5	15.98	20.75	2.38	2.24	2.3	5.24	72.09
422503150350	38	31.5	5	15.98	20.75	2.38	2.24	2.3	5.24	72.09

Blueprint

