

## Eye / Eye Crosby HG-226

---

### Product information



End fittings are quenched and tempered, bodies heat treated by normalizing. Turnbuckle eyes are forged elongated, by design, to maximize easy attachment in system and minimize stress in the eye. For turnbuckle sizes 6 mm through 64 mm, a shackle one size smaller can be reeved through eye.

**Standard:** According to Federal Specifications FF-T-791b.

... [Read more](#)

---

**Marking:** Logo, size and type.


**Finish:** Hot dipped galvanized.

**Note:** Turnbuckles recommended for straight or in-line pull only.

**Safety factor:** 5:1

# Eye / Eye Crosby HG-226

Blueprint



## Eye / Eye Crosby HG-226

### Technical data

Part code	WLL lb	Thread dia. & take up inch	A in	J open in	K closed in	M open in	N closed in	Rmm in	S in	X closed in	BB mm in	Weight lb
422100360100	800	5/16 x 4-1/2	0.31	13.94	9.41	14.49	9.96	0.95	0.44	2.2	4.57	0.49
422100540100	1,200	3/8 x 6	0.38	17.56	11.57	18.23	12.24	1.13	0.53	2.48	6.1	0.75
422100100100	2,200	1/2 x 6	0.5	19.92	13.94	20.83	14.8	1.41	0.71	3.56	6.02	1.72
422100100105	2,200	1/2 x 12	0.5	32.24	20.24	33.11	21.1	1.41	0.71	3.54	12.36	2.62
422100160100	3,500	5/8 x 6	0.63	21.73	15.71	22.72	16.73	1.8	0.88	4.33	6.02	2.76
422100160105	3,500	5/8 x 12	0.63	34.06	22.05	35.08	23.07	1.8	0.88	4.33	12.4	4.12
422100240100	5,200	3/4 x 6	0.75	23.23	17.24	24.49	18.5	2.09	1	5.12	6.14	4.21
422100240105	5,200	3/4 x 12	0.75	35.63	23.62	36.89	24.88	2.09	1	5.08	12.6	6.13
422100240106	5,200	3/4 x 18	0.75	47.64	29.65	48.9	30.91	2.09	1	5.12	18.54	7.83
422100330100	7,200	7/8 x 12	0.87	36.69	24.69	38.19	26.18	2.38	1.25	5.79	12.17	8.84
422100330105	7,200	7/8 x 18	0.87	49.17	31.18	50.67	32.68	2.38	1.25	5.79	18.62	11.51
422100450107	10,000	1 x 6	1	26.22	20.24	27.99	22.01	3	1.43	6.5	6.18	9.61
422100450105	10,000	1 x 12	1	38.23	26.22	40	27.99	3	1.43	6.5	12.17	12.96
422100450106	10,000	1 x 18	1	50.24	32.24	52.01	34.02	3	1.43	6.5	18.19	16.31
422100450100	10,000	1 x 24	1	62.83	38.86	64.61	40.59	3	1.43	6.06	24.84	20.15
422100690100	15,200	1-1/4 x 12	1.25	42.13	30.16	44.37	32.36	3.59	1.82	8.5	12.05	19.86
422100690105	15,200	1-1/4 x 18	1.25	54.13	36.14	56.38	38.39	3.63	1.82	8.5	18.07	23.81
422100690106	15,200	1-1/4 x 24	1.25	66.69	42.72	68.94	44.92	3.59	1.82	8.5	24.61	27.78
422100970100	21,400	1-1/2 x 12	1.5	44.25	32.24	46.73	34.72	4.09	2.12	9.45	12.32	28.66
422100970105	21,400	1-1/2 x 18	1.5	56.22	38.23	58.74	40.75	4.09	2.12	9.45	18.31	33.95
422100970106	21,400	1-1/2 x 24	1.5	68.86	44.84	71.38	47.36	4.09	2.12	9.45	24.92	39.46
422101270100	28,000	1-3/4 x 18	1.75	57.36	39.37	60.39	42.36	4.65	2.38	9.96	18.39	50.71
422101270105	28,000	1-3/4 x 24	1.75	69.37	45.39	72.36	48.39	4.65	2.38	9.96	24.37	58.2
422101680100	37,000	2 x 24	2	75.67	51.69	79.17	55.2	5.83	2.69	13.03	24.49	83.56
422102720100	60,000	2-1/2 x 24	2.5	79.17	55.2	83.19	59.17	6.5	3.12	13.78	24.61	148.59
422103400100	75,000	2-3/4 x 24	2.75	81.34	57.32	85.83	61.85	7.01	3.25	15.08	24.65	174.39