Industrial Rigging & Supply | Lifting Solutions Group Axel Johnson International

Swage Button S-409

Product information



General:

- Swage button terminations have an efficiency rating of 98% based on the catalog strength of wire rope.
- Special processed, low carbon steel.
- COLD TUFF for better swageability.
- Stamp for identification after swaging without concern for fractures (as per directions in the wire rope end terminations user's manual).

... *Read more*

Note: Length is measured from outside end of termination.

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International
Industrial Rigging & Supply

Swage Button S-409

Blueprint



Technical data

Part code	Rope Ø range mm	Size	Description	A in	B in	C in	D in	E in	Weight lb
12051040171	3	1 SB	1/8 - 1/4 Button	0.42	0.5	0.14	0.4	0.61	0.02
12051040215	5	3 SB	1/4 1st Stage	0.56	0.7	0.2	0.52	0.84	0.04
12051040251	6-7	5 SB	1/8 - 1/4 Button	0.68	1.06	0.31	0.58	1.32	0.08
12051040297	8	7 SB	3/8 1st Stage	0.88	1.13	0.36	0.77	1.33	0.16
12051040313	9-10	8 SB	3/8 1st Stage	0.88	1.48	0.42	0.77	1.69	0.15
12051040331	11	9 SB	1/2 1st Stage	1.13	1.63	0.48	1.03	1.94	0.3
12051040359	13	10 SB	5/8 Socket	1.31	1.89	0.55	1.16	2.17	0.5
12051040377	14	11 SB	9/16 - 5/8 Button	1.44	2.02	0.61	1.29	2.41	0.7
12051040395	16	12 SB	3/4 Socket	1.56	2.42	0.67	1.42	2.89	1
12051040411	18-20	13 SB	3/4 1st Socket	1.68	2.74	0.8	1.56	3.25	1.3
12051040439	22	14 SB	7/8 1st Stage	2	3.27	0.94	1.8	3.86	2.2
12051040457	25-26	15 SB	1 1st Stage	2.25	3.67	1.06	2.05	4.37	3.11
12051040475	28-29	16 SB	1-1/8 1st Stage	2.56	4.06	1.19	2.3	4.8	4.5
12051040493	31-32	17 SB	1-3/8 Socket	2.81	4.57	1.33	2.56	5.43	6.5

© November 2026 - All Rights Reserved