

## Shank Hook Crosby S-319BN

---

### Product information



- The most complete line of shank hoist hooks. Available 3/4 to 300 metric tons.
- Proper design, careful forging, and precision controlled quench and tempering give maximum strength without excessive weight and bulk.
- Every Crosby Shank Hook has a pre-drilled cam which can be equipped with a latch.
- Hooks incorporate QUIC-CHECK® deformation and angle indicators [... Read more](#)

---

**Material:** Bronze - Quenched and Tempered

**Safety factor:** 4:1

# Shank Hook Crosby S-319BN

## Blueprint



## Technical data

Part code	WLL (metric) tonnes	Hook ID Code	D, in	F in	G, in	H, in	J in	K in	L in	Mmm in	Omm in	Pmm in	Rmm in	T in	X mm in	Ymm in	Z mm in	AA*mm in	O2†† in	T2†† in
420500051410	0.5	†D	2.85	1.25	0.73	0.81	0.93	0.63	5.16	0.63	†23.6	1.96	2.34	0.97	0.59	2.07	0.69	1.25	-	-
420500061410	0.6	†F	3.17	1.38	0.84	0.94	0.97	0.71	5.67	0.71	†24.6	2.22	2.6	0.97	0.76	2.24	0.78	2	-	-
420500101410	1	†G	3.58	1.5	1	1.16	1.06	0.88	6.34	0.88	†26.9	2.44	2.76	1.03	0.72	2.6	0.88	2	-	-
420500141410	1.4	†H	4.02	1.62	1.14	1.31	1.19	0.94	7.13	0.94	†29.5	2.78	3.17	1.16	0.88	2.83	1	2	-	-
420500201410	2	†I	4.84	2.01	1.44	1.63	1.5	1.31	8.62	1.13	†34.5	3.46	3.86	1.53	1.16	3.44	1.25	2.5	1	1.5
420500351410	3.5	†J	6.3	2.5	1.82	2.07	1.78	1.66	10.43	1.44	1.61	4.61	4.76	1.94	1.41	3.84	1.56	3	1.31	1.88
420500501410	5	†K	7.56	2.99	2.26	2.64	2.4	1.88	12.52	1.63	2.09	5.24	5.87	2.46	1.81	4.37	1.94	3.98	1.81	2.25
420500651410	6.5	†L	8.35	3.25	2.6	2.93	2.62	2.19	16.1	1.94	2.26	5.94	6.38	2.6	2.01	7.01	2.19	3.98	2.01	2.31
420501001410	10	†N	10.35	4.25	3.01	3.5	3.41	2.7	18.15	2.38	3.01	6.89	8.15	2.81	2.56	7.01	2.64	5	2.75	2.56