



Shank Hook Crosby S-319BN

Product information

- The most complete line of shank hoist hooks. Available 3/4 to 300 metric tons.
- Proper design, careful forging, and precision controlled quench and tempering give maximum strength without excessive weight and bulk.
- Every Crosby Shank Hook has a pre-drilled cam which can be equipped with a latch.
- Hooks incorporate QUIC-CHECK® deformation and angle indicators.

Material: Bronze - Quenched and Tempered

Safety factor: 4:1

Part code	WLL (metric tonnes)	Hook ID Code	D, in	F in	G, in	H, in	J in	K in	L in	Mmm in	Omm in	Pmm in	Rmm in	T in	X mm in	Ymm in	Z mm in	AA*mm in	O2†† in	T2†† in
420500051410	0.5	†D	2.85	1.25	0.73	0.81	0.93	0.63	5.16	0.63	†23.6	1.96	2.34	0.97	0.59	2.07	0.69	1.25	-	-
420500061410	0.6	†F	3.17	1.38	0.84	0.94	0.97	0.71	5.67	0.71	†24.6	2.22	2.6	0.97	0.76	2.24	0.78	2	-	-
420500101410	1	†G	3.58	1.5	1	1.16	1.06	0.88	6.34	0.88	†26.9	2.44	2.76	1.03	0.72	2.6	0.88	2	-	-
420500141410	1.4	†H	4.02	1.62	1.14	1.31	1.19	0.94	7.13	0.94	†29.5	2.78	3.17	1.16	0.88	2.83	1	2	-	-
420500201410	2	†I	4.84	2.01	1.44	1.63	1.5	1.31	8.62	1.13	†34.5	3.46	3.86	1.53	1.16	3.44	1.25	2.5	1	1.5
420500351410	3.5	†J	6.3	2.5	1.82	2.07	1.78	1.66	10.43	1.44	1.61	4.61	4.76	1.94	1.41	3.84	1.56	3	1.31	1.88
420500501410	5	†K	7.56	2.99	2.26	2.64	2.4	1.88	12.52	1.63	2.09	5.24	5.87	2.46	1.81	4.37	1.94	3.98	1.81	2.25
420500651410	6.5	†L	8.35	3.25	2.6	2.93	2.62	2.19	16.1	1.94	2.26	5.94	6.38	2.6	2.01	7.01	2.19	3.98	2.01	2.31
420501001410	10	†N	10.35	4.25	3.01	3.5	3.41	2.7	18.15	2.38	3.01	6.89	8.15	2.81	2.56	7.01	2.64	5	2.75	2.56

Blueprint

