

Shank Hook Crosby S-319BN

Product information



- The most complete line of shank hoist hooks. Available 3/4 to 300 metric tons.
- Proper design, careful forging, and precision controlled quench and tempering give maximum strength without excessive weight and bulk.
- Every Crosby Shank Hook has a pre-drilled cam which can be equipped with a latch.
- Hooks incorporate QUIC-CHECK® deformation and angle indicators [... Read more](#)

Material: Bronze - Quenched and Tempered

Safety factor: 4:1

Shank Hook Crosby S-319BN

Blueprint



Technical data

Part code	WLL (metric tonnes)	Hook ID Code	D in	F in	G in	H in	J in	K in	L in	M in	O in	P in	R in	T in	X in	Y in	Z in	AA*mm in	O2†† in	T2†† in
420500051410	0.5	†D	2.85	1.25	0.73	0.81	0.93	0.63	5.16	0.63	†23.6	1.96	2.34	0.97	0.59	2.07	0.69	1.25	-	-
420500061410	0.6	†F	3.17	1.38	0.84	0.94	0.97	0.71	5.67	0.71	†24.6	2.22	2.6	0.97	0.76	2.24	0.78	2	-	-
420500101410	1	†G	3.58	1.5	1	1.16	1.06	0.88	6.34	0.88	†26.9	2.44	2.76	1.03	0.72	2.6	0.88	2	-	-
420500141410	1.4	†H	4.02	1.62	1.14	1.31	1.19	0.94	7.13	0.94	†29.5	2.78	3.17	1.16	0.88	2.83	1	2	-	-
420500201410	2	†I	4.84	2.01	1.44	1.63	1.5	1.31	8.62	1.13	†34.5	3.46	3.86	1.53	1.16	3.44	1.25	2.5	1	1.5
420500351410	3.5	†J	6.3	2.5	1.82	2.07	1.78	1.66	10.43	1.44	1.61	4.61	4.76	1.94	1.41	3.84	1.56	3	1.31	1.88
420500501410	5	†K	7.56	2.99	2.26	2.64	2.4	1.88	12.52	1.63	2.09	5.24	5.87	2.46	1.81	4.37	1.94	3.98	1.81	2.25
420500651410	6.5	†L	8.35	3.25	2.6	2.93	2.62	2.19	16.1	1.94	2.26	5.94	6.38	2.6	2.01	7.01	2.19	3.98	2.01	2.31
420501001410	10	†N	10.35	4.25	3.01	3.5	3.41	2.7	18.15	2.38	3.01	6.89	8.15	2.81	2.56	7.01	2.64	5	2.75	2.56