

Shank Hook SHUR-LOC, Crosby S-1318A

Product information



All SHUR-LOC® hooks have the following features:

- Recessed trigger design is flush with the hook body, protecting the trigger from potential damage.
- Easy to operate with enlarged thumb access.
- Positive lock latch is self-locking when the hook is loaded.
- The SHUR-LOC® hook, if properly installed and locked, can be used for personnel lifting applications and meets the intent of OSHA Rule 1926.1431(g)(1)(i)(A) and 1926.1501(g)(4)(iv)(B).
- Fatigue rated to 20,000 cycles at 1-1/2 times the Working Load Limit* ... [Read more](#)

Material: Forged alloy steel, Quenched & Tempered.


Marking: CE-marked

Safety factor: 4:1

Grade: 10

Shank Hook SHUR-LOC, Crosby S-1318A

Blueprint



Technical data

Part code	Chain diameter in	WLL lb	A in	B in	C in	D, in	E in	F in	G, in	J in	L in	AA*mm in	Weight lb
402300151670	-	3,200	0.79	2.17	3.31	0.79	2.6	0.67	6.26	0.63	1.13	1.5	0.99
402300261670	1/4-5/16	5,700	1	2.4	4.17	1.1	3.5	0.87	7.68	0.81	1.38	2.01	1.98
402300401670	3/8	8,800	1.14	2.95	5.16	1.17	4.41	1.1	9.25	0.94	1.83	2.5	3.55
402300701670	1/2	15,000	1.34	3.35	6.3	1.67	5.43	1.26	11.34	1.16	2.11	3	7.01