

## Crosby Screw Clamp IPSC10 – Not for Lifting



### Product information

The IPSC10 screw style clamp is suitable for use in positioning, pulling and turning steel plates and sections.

#### Features:

- Available in capacities of 1.5 and 3 metric tons.
- Jaw openings available: 0 to 60mm
- Suitable for steel with a surface hardness up to 300 HV10.
- Forged alloy steel body for strength and smaller size. Forged alloy components, where required.
- Individually Proof Tested to 2 times the Working Load Limit with certification.
- User manual with test certificate is included with each clamp.
- Maintenance and repair kits are available.

**Material:** Alloy steel.

**Marking:** CE-marked, Logo, WLL, serial number, proofload test date and jaw opening.

**Temperature range:** -40°C up to +100°C

**Warning:** Not to be used as a lifting clamp.

Part code	WLL (metric tonnes)	Jaw width in	Model	A in	B in	C in	D, in	E in	F in	G, in	H, in	J in	K in	Weight lb
502100150400270	1.5	0-1.57	1.5-IPSC	0-1.57	3.58	5.63	9.88	1.73	6.14	1.97	1.77	0.63	2.56	10.14
502100300600270	3	0-2.36	3-IPSC	0-2.36	4.29	6.89	12.2	2.01	7.87	2.44	2.17	0.75	3.27	18.52

# Blueprint

