Industrial Rigging & Supply | Lifting Solutions Group Axel Johnson International

Vertical Lifting Clamps Non Marring- IPNM10 series

Product information

The IPNM10 series vertical lifting clamps are used for lifting, turning, moving or vertical transfer of sheet, plates, or fabrications from horizontal to vertical and down to horizontal (180°) as needed without marring the surface of the material. Materials such as aluminum, stainless steel, painted materials, aircraft skins, composite material, glass, plastic, etc., can be lifted without marring or scratching the material surface. Available in a variety of models:
IPNM10(N) - standard model.
IPNM10P - Equiped with protection cap. Reduces risk of damaging surrounding plates/material.
IPNM10J - clamps with larger jaw opening.
IPNM10JC - Special clamp with curved jaws. Only available on request.

Features:
• Available in capacities of 0.5 , 1 and 2 metric tons.
• Wide variety of jaw openings available: 0 to 40mm.
• Welded alloy steel body for strength and smaller size. Forged alloy components, where required.
• Individually Proof Tested to 2 times the Working Load Limit with certification.
• User manual with test certificate is included with each clamp.
• Full 180° turning range for material transfer, turning or moving.
• Lock open, lock closed ability with latch for pretension on material and then release of material.
• There is no minimum WLL required.
• Maintenance and repair kits are available.
• All sizes are RFID EQUIPPED.

... *Read more*

Material: Alloy steel.
Marking: According to standard, CE-marked, WLL, Logo, Jaw opening, Serial number
Temperature range: -20°C up to +70°C
Standard: EN 13155
Warning: To be handled material must be clean and dry.

© September 2026 - All Rights Reserved

Industrial Rigging & Supply | Lifting Solutions Group Axel Johnson International

Vertical Lifting Clamps Non Marring- IPNM10 series

Blueprint



Technical data

Part code	WLL (metric) tonnes	Jaw width in	Model	A in	B in	C in	D in	E in	F in	G in	H in	K in	Weight lb
502100050100180	0.5	0-0.39	0,5-IPNM10N	0-0.39	3.31	6.26	9.25	1.57	5.04	2.36	1.65	0.43	5.95
502100050100184	0.5	0-0.39	0.5-IPNM10P	0-0.39	3.23	6.18	8.7	1.57	5.71	2.68	1.89	0.43	6.17
502100100200180	1	0-0.79	1-IPNM10N	0-0.79	3.82	8.23	10.94	1.57	7.24	3.15	2.2	0.43	9.7
502100100200184	1	0-0.79	1-IPNM10P	0-0.79	3.82	7.68	10.87	1.57	8.07	3.23	2.6	0.43	9.92
502100100370185	1	0.79-1.46	1-IPNM10NJ	0.79-1.46	3.82	8.66	12.64	1.57	7.87	3.15	2.2	0.43	10.36
502100100250186	1	0-0.98	1-IPNM10NJ1	0-0.98	3.82	9.37	13.82	1.57	8.39	3.15	2.48	0.43	12.13
502100200400180	2	0-1.57	2-IPNM	0-1.57	6.02	10.16	15.59	2.76	11.65	3.94	6.34	0.63	31.97

© September 2026 - All Rights Reserved