



Swivel Eye / Hook Crosby S6

Product information

Design: Swivel with eye and hook equipped with tapered roller thrust bearing.

Features:

- Suitable for frequent rotation under load.
- All swivels individually Proof Tested to 2 times the Working Load Limit.
- Pressure lube fitting provided
- All hooks furnished with latches
- Other types and capacities up to 1250 t available on demand.

Marking: CE-marked

Note: Always check before use if your steel wire rope is suitable for use with a swivel.

Warning: Not to be used on demolition- (wrecking-) balls!

Safety factor: 5:1

Part code	Diameter mm	WLL (metric) tonnes	Rope Ø mm	Swivel No	E mmin	F mmin	G mmin	Lin	M mmin	P mmin	Q mmin	R mmin	S mmin	T mmin	V mmin	Weight lb
422500300300	-	3	13	3-S-6	11.5	4.84	2.76	1.5	1.38	1.42	0.75	1.02	1.1	1.22	1.1	9.33
422500500300	-	5	16	5-S-6	13.07	6.3	2.99	1.93	1.65	1.81	0.98	1.26	1.22	1.22	1.42	14.24
422500850300	0	8.5	19	8-S-6	16.06	7.56	4.02	2.44	2.2	2.24	1.22	1.38	1.61	1.5	1.61	31.97
422501000300	-	10	22	10-S-6	19.13	8.35	4.49	2.6	2.4	2.6	1.65	1.65	2.76	1.85	1.93	45.42
422501500300	-	15	26	15-S-6	21.26	10.35	5	2.8	2.4	2.99	1.93	2.01	2.76	2.13	2.36	63.05
422502500300	-	25	-	25-S-6	27.52	13.62	5.98	3.43	3.62	3.66	2.24	2.28	3.86	2.36	2.99	134.48
422503500300	-	35	-	35-S-6	30.71	14.06	6.5	3.86	3.74	4.57	2.24	2.28	3.86	2.36	3.19	216.05
422504500300	-	45	-	45-S-6	35.71	15.43	7.01	4.76	4.25	5.08	2.48	2.52	4.02	2.99	3.23	268.96

Blueprint

