



Swivel Eye / Jaw Crosby S4

Product information

Design: Swivel with eye and jaw equipped with tapered roller thrust bearing.

Features:

- Suitable for frequent rotation under load.
- All swivels individually Proof Tested to 2 times the Working Load Limit.
- Pressure lube fitting provided.
- All jaws complete with bolts, nuts and cotter pins.
- Other types and capacities up to 1250 t available on demand.

Marking: CE-marked

Note: Always check before use if your steel wire rope is suitable for use with a swivel.

Warning: Not to be used on demolition- (wrecking-) balls!

Safety factor: 5:1

Part code	Rope Ø range mm	WLL (metric) tonnes	Swivel No	C mmin	G mmin	H mmin	J mmin	K mmin	N mmin	O mmin	Q mmin	R mmin	S mmin	T mmin	Weight lb
422500300110	13	3	3-S-4	9.33	2.76	0.75	0.88	1.62	1.31	1	0.75	1.03	1.12	1.25	8.99
422500500110	16	5	5-S-4	10.08	2.99	0.88	1	2.24	1.62	1.12	1	1.28	1.25	1.25	12.35
422500850110	19	8.5	8-S-4	12.24	4.02	1	1.56	2.81	2.13	1.38	1.25	1.41	1.62	1.5	29.1
422501000110	22	10	10-S-4	16.1	4.49	1.5	1.75	3.39	3.5	1.75	1.69	1.69	2.76	1.88	44.09
422501500110	26	15	15-S-4	16.73	5	1.5	1.75	3.39	3.5	1.75	1.94	2.03	2.76	2.13	61.07
422502500110		25	25-S-4	21.5	5.98	2.01	2.01	4.61	3.68	2.38	2.24	2.3	3.88	2.38	134.48
422503500110		35	35-S-4	21.5	6.5	2.01	2.01	4.61	3.68	2.38	2.24	2.3	3.88	2.38	149.91
422504500110		45	45-S-4	25.87	7.01	2.24	2.5	5	4.02	2.99	2.5	2.54	4.02	2.99	224.87

Blueprint

